

Socket outlet

Socket outlet, Jussi, Schuko, 4-gang, shuttered, screwless terminals



Type: 404EA

Product ID: 2TKA001001G1

GTIN: 6418677335822



There is 2 times 2-gang socket outlet inserts in one unit. The socket outlet inserts are internally connected. In one socket outlet insert there are terminals for each contact of the socket outlet for max 4 rigid wires. No X-terminals.

Technical specification

Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

Classification

Suitable for degree of protection (IP):	IP21
---	------

Packing

Package:	1/20
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

Product Card

Socket outlet, Jussi, Schuko, 4-gang, shuttered, screwless terminals



ETIM Class:	EC000125
Number of active pins (round):	2
With signal lamp:	No
Number of units:	4
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	No
With enhanced contact protection:	Yes
Label space/information surface:	No
Colour:	White
RAL-number (similar):	9010
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Surface mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	No
With loop through function:	No
With on/off switch:	No

Product Card

Socket outlet, Jussi, Schuko, 4-gang, shuttered, screwless terminals



Rotated central insert:	No
Frequency:	50 Hz
Device width:	110 mm
Device height:	42 mm
Device depth:	98 mm