


Product Information

BKT 585 U/FTP cat. 6_A installation cable

Card No.: PI_BKT585 U/FTP_01.17



Eca
CPR

Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)

IEEE 802.3: 10BASE-T, 100BASE-T, 1000BASE-T, 2.5GBASE-T, 5GBASE-T, 10GBASE-T

IEEE 802.5: 16MB, ISDN, TPDDI, ATM

Power over Ethernet (PoE / PoE+)

Standards

- EN 50173-1
- EN 50288-11-1
- EN 50399
- EN 50575
- ISO/IEC 11801
- IEC 61156-5
- ANSI/TIA 568-C.2
- IEEE 802.3at

Flame Resistance

LSHF (LSOH, FRNC): IEC 60332-1, IEC 61034, IEC 60754-2

CPR: Class Eca - EN 50399, EN 50575

Product Information

BKT 585 U/FTP cat. 6_A installation cable

Card No.: PI_BKT585 U/FTP_01.17

Construction

Conductor	Bare copper wire \varnothing 0,55 mm (AWG 23)
Insulation	Polyethylene \varnothing 1,4mm
Twisting	2 cores to the pair
Cable lay up	4 pairs to the core
Screen	Al-laminated plastic foil around each pair, drain wire AWG 26 tinned
Sheath	LSHF (LSOH, FRNC) blue RAL 5024

Mechanical Properties

Bending radius	installation	4 x D
	installed	8 x D
Temperature range	during operation	-20°C to +60°C
	during installation	0°C to +50°C

Technical Data

Product code	Cable type	Product name	Outer diameter (mm)	Fire load (MJ/km)	Fire load (kWh/m)	Weight (kg/km)	Tensile force (N)	NVP (%)
10157515.500	J-02YSCH 4x2x0.55	Cable U/FTP LSHF cat.6A BKT 585 wire blue 23AWG	7,3	732	0,203	45	100	75