SCHUKO® socket 16 A / 250 V ~ with 1-gang / 2-way switch 10 AX / 250 V ~, screw terminals, duroplastic, AS range, white



Reference number:	AS 5576 U WW
EAN/GTIN:	4011377991903
Color:	white
Material:	duroplastic
Power SBL (self-ballasted lamps):	max. 100 W

Duroplastic (scratch-proof) glossy
to be installed into one flush box with 60 mm Ø
with integrated frame
with screw terminals for rigid and flexible wires up to 2.5 mm^2

without claws: ref.-no. with additional "E", e.g.: AS 5576 EU
dimensions: 80.5 x 105 mm

(2-way switch circuit possible with ref.-no. 506 U.)

Dimensions



Notice!
Installation only by persons with relevant electrical knowledge and experience!*)
Use only with original JUNG product components approved for this article.

ALBRECHT JUNG GMBH & CO. KG
Volmestraße 1
58579 Schalksmühle
Phone +49 (0) 23 55/80 60
E-Mail kundencenter@jung.de

By inappropriate installation you endanger
• your own life,
• the life of the user of the electrical appliance.
By inappropriate installation you risk a high loss by damage, e.g. risk by fire.
You assume personal liability in cause of injury to persons or damage of appliances.
Please contact a skilled electrician!

***) Required technical knowledge for installation:**
For installation, especially the following technical knowledge is required:
• the 5 important safety rules: disconnect from mains, secure against reconnecting, verify parts are free of voltage, ground and short-circuit, cover or block off adjacent live parts
• select adequate tools, measuring devices and personal protective equipment
• evaluate measuring results
• selection of the electrical installation material to secure switch-off conditions
• IP protection levels
• installation of the electrical installation material
• type of electric power grid (TN system, IT system, TT system) and the resultant connection terms (common grounding, protective ground, required additional action etc.)

ALBRECHT JUNG GMBH & CO. KG
Volmestraße 1
58579 Schalksmühle
Phone +49 (0) 23 55/80 60
E-Mail kundencenter@jung.de