3-gang SCHUKO® socket, wired, 16 A 250 V ~, horizontal , IP 44, WG 800



Reference number:	8230 W
EAN/GTIN:	4011377658301
Color:	grey
Material:	thermoplastic

Degree of protection IP44 is ensured.

for horizontal installation, housing 226 x 75 x 58 mm
wired
with screwless terminals for rigid and untreated flexible wires up to 2.5 mm^2

(3 single covers)
Sockets may be replaced by switches , push-buttons, pilot lights or sockets with safety lock

Dimensions



Notice!
Installation only by persons with relevant electrical knowledge and experience!*)
Use only with original JUNG product components approved for this article.

ALBRECHT JUNG GMBH & CO. KG
Volmestraße 1
58579 Schalksmühle

Phone +49 (0) 23 55/80 60
E-Mail kundencenter@jung.de

By inappropriate installation you endanger
• your own life,
• the life of the user of the electrical appliance.
By inappropriate installation you risk a high loss by damage, e.g. risk by fire.
You assume personal liability in cause of injury to persons or damage of appliances.
Please contact a skilled electrician!

***) Required technical knowledge for installation:**
For installation, especially the following technical knowledge is required:
• the 5 important safety rules: disconnect from mains, secure against reconnecting, verify parts are free of voltage, ground and short-circuit, cover or block off adjacent live parts
• select adequate tools, measuring devices and personal protective equipment
• evaluate measuring results
• selection of the electrical installation material to secure switch-off conditions
• IP protection levels
• installation of the electrical installation material
• type of electric power grid (TN system, IT system, TT system) and the resultant connection terms (common grounding, protective ground, required additional action etc.)