KNX USB data interface, rail mounting device, 2 rail units



Reference number:	2131 USBS REG
EAN/GTIN:	4011377171770

rail mounting device, 2 rail units

Intended use
- Connecting PCs to KNX systems
- Addressing, programming and diagnostics of KNX devices
- KNX Data Secure compatible with ETS 5.7.3 or higher
- Support of long frames for ETS5
- Mounting on DIN rail according to EN 60715 in distribution box

Product characteristics
- Connection with device connection terminal
- Electrical isolation of KNX and USB
- Temporary operation in unmounted condition permissible
- The firmware in the USB data interface can be updated via the ETS product database
- Power supply exclusively via the USB port

Technical data

KNX medium:	TP 256
Power supply:	via USB port of the PC
Connection	
Connection, KNX:	connection terminal
USB port:	USB port, type B
Transfer rate:	9600 Baud
Transmission protocol:	compatible with USB 1.1/2.0
Length of USB cable:	max. 5 m
Ambient temperature:	-5 ... +45 °C
Storage temperature:	-25 ... +70 °C
Protection class:	II
Mounting width:	36 mm (2 rail units)

ALBRECHT JUNG GMBH & CO. KG
Volmestraße 1
58579 Schalksmühle
Phone +49 (0) 23 55/80 60
E-Mail kundencenter@jung.de

Dimensions



ALBRECHT JUNG GMBH & CO. KG
Volmestraße 1
58579 Schalksmühle

Phone +49 (0) 23 55/80 60
E-Mail kundencenter@jung.de

Assembly


ALBRECHT JUNG GMBH & CO. KG | Volmestraße 1 | 58579 Schalksmühle | GERMANY
03/2023


ALBRECHT JUNG GMBH & CO. KG | Volmestraße 1 | 58579 Schalksmühle | GERMANY
03/2023