41ALM172

ADDITIONAL POWER SUPPLY UNIT FOR 41CPE118



LOGIFIRE series additional outdoor power supply unit, designed to supply addressed control panel 41CPE118 with additional power. Grey metal case with IP30 protection rating (430x330x150 mm), with the same dimensions as all Comelit LOGFIRE series control panels and boxes to guarantee installation in modular structures. 5A power supply unit with 12 V output for battery, maximum battery capacity 2 x 12 V / 18 Ah. Continuous monitoring available by activating the “Monitor external power supply unit” option in the 41CPE118 fire panel menu. Approved to EN54-4.

41ALM172

ADDITIONAL POWER SUPPLY UNIT FOR 41CPE118

MAIN FEATURES	
Installation in modular structures	Yes
EN regulations	EN54-4

HARDWARE SPECIFICATIONS	
Height (mm)	330
Width (mm)	430
Depth (mm)	150
IP protection rating	IP30
Type of finishing materials	Metallic
Product color	Grey, RAL 7045
Product weight without battery (g)	6500
Operating temperature (°C)	-5 ÷ 50
Operating humidity (RH max @40°C) (%)	0 ÷ 96

ELECTRICAL SPECIFICATIONS	
Power supply	110÷230VAC (± 10%)
Output voltage range (VDC)	9.9 ÷ 14.2
Maximum current supplied by the power supply	7A@1 battery, 14A@2 batteries
Charger output	13.65Vdc ±1%@20°C, max. 2A

GENERAL DATA	
Backup power supply (batteries not supplied)	2 x 12VDC - 18Ah
Compatible control panels	41CPE118
Model	Additional power supply unit, LOGIFIRE series
Flush-mounted	Yes, Art. 48BIA100

The technical specifications are subject to change without prior notice.