K41VAD100L

BASE WITH STROBE EN54-23 + SOUND BASE EN54-3



Kit consisting of low-profile base with visual indication certified to EN54-23 (41VAD100) and audible indication device certified to EN54-3 (41SAB101), for indoor use and ceiling-mounted. With the same features as base 41RBX020, base 41VAD100 incorporates 3 white flashing lights arranged uniformly so as to guarantee 360° visibility. Maximum absorption with flash and high volume 29 mA. Total diameter: 160 mm. White RAL 9016. Material: ABS. Certification according to EN54-3, EN54-17 and EN54-23.

K41VAD100L

BASE WITH STROBE EN54-23 + SOUND BASE EN54-3

MAIN FEATURES	
Model	Kit with flashing light base and sounder base
Number of tones available (n°)	32
Isolator	Yes
EN regulations	EN54-17, EN54-3, EN54-23

HARDWARE SPECIFICATIONS	
IP protection rating	IP21C
Type of finishing materials	ABS
Installation	Ceiling mount
Product color	White RAL9016
Coverage	C-3-6
Flashing frequency (Hz)	0.5
Visual indication colour	White
Cross-section for terminals (mm)	0.4 ÷ 1.5
Operating temperature (°C)	-10 ÷ 50
Operating humidity (RH max @40°C) (%)	0 ÷ 93
Height (mm)	40
Diameter (mm)	162
Product weight (g)	215

ELECTRICAL SPECIFICATIONS	
Supply voltage	20÷32 VDC
Rated absorption (stand-by)	1mA
Max. abs. (mA - visual/audible part)	<29
Sound power (other tones) high volume (dB@1m)	~ 87dB (A) ± 3dB @ 1m
Sound power (other tones) low volume (dB@1m)	~ 81dB (A) ± 3dB @ 1m

The technical specifications are subject to change without prior notice.

K41VAD100L

BASE WITH STROBE EN54-23 + SOUND BASE EN54-3

ELECTRICAL SPECIFICATIONS

Sound power (main tone 27) high volume (dB@1m)	~ 88dB (A) ± 3dB @ 1m
Sound power (main tone 27) low volume (dB@1m)	~ 81dB (A) ± 3dB @ 1m

The technical specifications are subject to change without prior notice.