41RML100B

ADDRESSABLE MULTI-SENSOR DETECTOR, BLACK



41RML100B

ADDRESSABLE MULTI-SENSOR DETECTOR, BLACK

MAIN FEATURES	
Model	Multi-criteria smoke/heat detector+ rate of rise detector, LOGIFIRE series
Backwards compatible with ATENA series control panels	Yes
Sensitivity level settings	High/Normal*/Medium/Low (optics) - A1R (thermal - 58º, RoR)
LED indicators	2, visibility 360°
Conformity class EN54-5	A1/R
Isolator	Yes
Settling time on power-up (s) (secs)	30
EN regulations	EN54-5, EN54-7, EN54-17

HARDWARE SPECIFICATIONS	
IP protection rating	IP30
Type of finishing materials	ABS
Product color	Black RAL9005
Compatible base	41RBX020
Operating temperature (°C)	-10 ÷ 60
Operating humidity (RH max @40°C) (%)	0 ÷ 96
Cross-section for terminals (mm)	0.4 ÷ 2.5
Width (mm)	108
Height base included (mm)	48
Product weight (g)	125

ELECTRICAL SPECIFICATIONS	
Power supply	16 - 32VDC (Nom. 27VDC)
Consumption during communication	<310uA@27VDC
Rated absorption (stand-by)	<190µA@27VDC
Consumption in alarm status	6.5mA

The technical specifications are subject to change without prior notice.

41RML100B

ADDRESSABLE MULTI-SENSOR DETECTOR, BLACK

ELECTRICAL SPECIFICATIONS

Output in alarm status for remote indication	7.5mA@7.5VDC

The technical specifications are subject to change without prior notice.