41SAB101B

ADDRESSABLE SOUND BASE EN54-3, BLACK



41SAB101B

ADDRESSABLE SOUND BASE EN54-3, BLACK

MAIN FEATURES	
Model	Base with siren, LOGIFIRE series
Backwards compatible with ATENA series control panels	Yes
Number of tones available (n°)	32
Isolator	Yes
EN regulations	EN54-3, EN54-17

HARDWARE SPECIFICATIONS	
Compatible base	41RBX020, 41VAD100
IP protection rating	IP21C
Type of finishing materials	ABS
Installation	Ceiling mount
Product color	Black RAL9005
Cross-section for terminals (mm)	0.4 ÷ 2.5
Operating temperature (°C)	-10 ÷ 55
Height base included (mm)	38
Diameter (mm)	121
Product weight (g)	125

ELECTRICAL SPECIFICATIONS	
Supply voltage	16 – 32 V CC (Nom. 27 V CC)
Rated absorption (stand-by)	470uA@27VDC
Max. abs. (other tones) high volume (with only audio active)	9,8 mA a 27 V CC
Max. abs. (other tones) low volume (with only audio active)	2,8 mA a 27 V CC
Max. abs. main tone 27 high volume with only audio active	9,8 mA a 27 V CC
Max. abs. main tone 27 low volume with only audio active	2,8 mA a 27 V CC

The technical specifications are subject to change without prior notice.

41SAB101B

ADDRESSABLE SOUND BASE EN54-3, BLACK

ELECTRICAL SPECIFICATIONS

Sound power (other tones) high volume (dB@1m)	~ 87dB (A) ± 3dB @ 1m
Sound power (other tones) low volume (dB@1m)	~ 81dB (A) ± 3dB @ 1m
Sound power (main tone 27) high volume (dB@1m)	~ 88dB (A) ± 3dB @ 1m
Sound power (main tone 27) low volume (dB@1m)	~ 81dB (A) ± 3dB @ 1m

The technical specifications are subject to change without prior notice.