41SPG000

PROGRAMMER FOR ADDRESSABLE DEVICES



The programmer 41SPG000 is the instrument used to assign addresses to all the devices connected in the loop (detectors, modules, manual call points and audible/visual alarms). It can read and write the addresses and to set the parameters of the detectors and modules. It is supplied with a 230 Vac, 50 Hz/ 1.5-12 Vdc, 500 mA, 6 VA (max.) power supply unit and 2 cables for connection of the modules and manual call points. It can also be powered by 4 x 1.5 V AA batteries. The detectors and audible and visual alarm devices can be directly connected to the base on the upper part of the programmer. Dimensions: 255x102x65 mm. Weight: 260 g.

41SPG000

PROGRAMMER FOR ADDRESSABLE DEVICES

MAIN FEATURES	
Display	Yes
Number of addresses available (n°)	250
Multi-language display menu	Yes

HARDWARE SPECIFICATIONS	
Product color	White
Product weight (g)	260
Operating temperature (°C)	-5 ÷ 40
Operating humidity (RH max @40°C) (%)	0 ÷ 96

ELECTRICAL SPECIFICATIONS	
Supply voltage	4.2÷8 VDC
Secondary power supply	4 x 1.5 V batteries, type AA

GENERAL DATA	
Type of finishing materials	ABS

The technical specifications are subject to change without prior notice.