UT9260M

DIGITAL DIRECTORY MODULE WITH DISPLAY, ULTRA



Digital directory module for Ultra entrance panel, compatible with all systems. Bluetooth connection for managing names in the directory using the installer's MyComelit app. Buttons for user selection and calling. Option of customising one button for direct calls to the switchboard, commercial activities, activation of an automated opening or a light. Equipped with a 3.5" colour graphic display. Can be paired with the numeric keypad module to directly call the user when the relevant code is known, or for the access control function with activation of the audio or audio/video module outputs and the system actuators. Dimensions: 100x90x35 mm.

AWARDS

UT9260M

DIGITAL DIRECTORY MODULE WITH DISPLAY, ULTRA

GENERAL DATA	
Type	Modular
Height (mm)	90
Width (mm)	100
Depth (mm)	35
Product weight (g)	400
Type of finishing materials	Polycarbonate
Product color	Black RAL9005, Transparent
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS	
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes

DISPLAY	
Display type	Graphic LCD
Display size (")	3.5
Resolution (pixel)	320x240

ELECTRICAL CHARACTERISTICS	
Type of power supply	Power supply from video door entry bus
Supply voltage	33VDC
Absorption in stand-by (W)	1.3
Maximum absorption (W)	2

The technical specifications are subject to change without prior notice.

UT9260M

DIGITAL DIRECTORY MODULE WITH DISPLAY, ULTRA

HARDWARE FEATURES	
Call type	Digital
Type of buttons	Mechanical
Number of push-buttons (n°)	4
Backlight colour	Black
Clamps	D+ D- GND

SETTINGS	
Backlighting display	Yes
Backlight brightness	Yes

NETWORK AND COMMUNICATION PROTOCOLS	
Bluetooth	Yes

PROGRAMMING MODE	
ViP Manager software	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES	
IP protection rating	IP65
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), RED 2014/53/UE (EN 62311:2008, EN 62368-1:2014, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1)

MAIN FUNCTIONS	
No. of storable users (n°)	1500
Visual indications of system status	Yes
Customizable welcome message	Yes

The technical specifications are subject to change without prior notice.

UT9260M

DIGITAL DIRECTORY MODULE WITH DISPLAY, ULTRA

MAIN FUNCTIONS	
	Yes

The technical specifications are subject to change without prior notice.