CCTV

NVR/AHDVR

NIPNVR004N06PA

4CH POE NVR, NEXT SERIES, NDAA, HDD 1TB



NEXT SERIE

Network video recorder (NVR) for 4 IP channels (4 PoE), NDAA compliant, max. resolution 6 MP, video compression H.265S / H.265+ /H.265 /H.264, dual streaming, bandwidth 40 Mbps. Supports all DVA video analysis functions for the connected cameras. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Remote control via Comelit CCTV APP and Comelit CCTV Manager software. 48 V power supply unit included. This NVR connects to Comelit servers protected by AWS services.

AWARDS

NDAA COMPLIANT

NIPNVR004N06PA

4CH POE NVR, NEXT SERIES, NDAA, HDD 1TB

MAIN FEATURES	
Video inputs	4 PoE (6MP/5MP/4MP/3MP/1080P/960P/720P/D1/CIF)
Main video output	1 (VGA), 1 (HDMI), 1920x1080
Video compression	H.265S / H.265+ / H.265 / H.264
Playback / recording frame rate	30fps@6MP
HDD supplied size	1TB (10TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS	
Recording methods	Automatic, manual, programmed, event
Maximum number of channels being played simultaneously	1@6MP, 4@Full HD
Protocols supported	DDNS, DHCP, HTTP, HTTPS, SMTP, TCP/IP, ONVIF, SNMP
IP assignment	DHCP, manual
Max bandwidth (Mbps)	40
Remote control via browser	Edge, Firefox, Chrome, Safari
Remote control by software	Comelit CCTV Manager
Remote control by mobile	APP Comelit CCTV
Users connected at the same time	32
Main functions	Video analysis (only with dedicated cameras), Alarm system function

FUNCTIONS	
Motion detection	Yes

HARDWARE SPECIFICATIONS	
Type of connections/ports	1xEthernet 10/100 Mbit/s, 2xUSB 2.0, 4 x Ethernet PoE 10/100 Mbit/s
Fanless	Yes

GENERAL DATA	
Machine absorption (no HDD) (W)	5
Maximum absorption per POE port (W)	30

The technical specifications are subject to change without prior notice.

NIPNVR004N06PA

4CH POE NVR, NEXT SERIES, NDAA, HDD 1TB

GENERAL DATA	
POE total power (W)	40
Maximum distance in long range mode (CAT5e/CAT6) (m)	150
Power supply voltage (VDC)	48
Height (mm)	42
Width (mm)	255
Depth (mm)	222
Product weight (g)	1.6
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-10 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 90
Supplied accessories	Power supply, Mouse

The technical specifications are subject to change without prior notice.