Specifications



Photo is representative





Eaton 014376

Eaton Moeller® series ZE Overload relay, Ir= 0.6 - 1 A, 1 N/O, 1 N/C, Direct mounting

General specifications	
PRODUCT NAME	Eaton Moeller® series ZE Thermal overload relay
CATALOG NUMBER	014376
MODEL CODE	ZE-1,0
EAN	4015080143765
PRODUCT LENGTH/DEPTH	52 mm
PRODUCT HEIGHT	65 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.075 kg
CERTIFICATIONS	CSA CSA Class No.: 3211-03 UL 508 VDE 0660 UL IEC/EN 60947-5-1 UL File No.: E29184 IEC/EN 60947 CE CSA-C22.2 No. 14 CSA File No.: 012528 IEC/EN 60947-4-1 UL Category Control No.: NKCR

Powering Business Worldwide

Contacts

NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF	Does not apply, since the

SWITCHING DEVICES AND COMPONENTS	entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	4.8 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.6 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	1 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Electrical rating

CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	6 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 120 V	1.5 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	1.5 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	0.7 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V	0.5 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.4 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.2 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	0.9 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	0.75 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
SAFE ISOLATION	300 V AC, Between auxiliary contacts and main contacts, According to EN 61140 250 V AC, Between auxiliary contacts, According to EN 61140 300 V AC, Between main circuits, According to EN 61140
SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	0.6 A, 600V AC, (UL/CSA) 1.5 A, 240V AC, (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	D300, AC operated (UL/CSA) R300, DC operated (UL/CSA)

Features & functions

FEATURES	Reset pushbutton manual/auto Phase-failure sensitivity (according to IEC/EN 60947, VDE 0660 Part 102) Test/off button Trip-free release

General information

AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
CLASS	CLASS 10 A / IEC 60947-4-1, 8.2.1.5.1.1. c) 4 min
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
DEGREE OF PROTECTION	IP00
MOUNTING METHOD	Direct attachment Direct mounting
OVERLOAD RELEASE CURRENT SETTING - MAX	1 A
OVERLOAD RELEASE CURRENT SETTING - MIN	0.6 A
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	ZE overload relays for mini contactor relays
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC 4000 V (auxiliary and control circuits)
SHOCK RESISTANCE	10 g, Mechanical, Sinusoidal, Shock duration 10 ms
SUITABLE FOR	Branch circuits, (UL/CSA)
TEMPERATURE COMPENSATION	Continuous ≤ 0.25 %/K, residual error for T > 40°

Short-circuit rating

SHORT-CIRCUIT CURRENT RATING (BASIC RATING)	5 kA, SCCR (UL/CSA) 3 A, max. Fuse, SCCR (UL/CSA) 15 A, max. CB, CB for max. 480 V, SCCR (UL/CSA)
SHORT-CIRCUIT PROTECTION RATING	4 A gG/gL, Fuse, Type “2” coordination 20 A gG/gL, Fuse, Type “1” coordination Max. 4 A gG/gL, Fuse, Auxiliary contacts Information on Type "1" and Type"2" coordination applies to 100 kA and 690 V

Terminal capacities

SCREW SIZE	M3.5, Terminal screw
SCREWDRIVER SIZE	2, Terminal screw, Pozidriv screwdriver 0.8 x 5.5 mm, Terminal screw, Standard screwdriver
STRIPPING LENGTH (CONTROL CIRCUIT CABLE)	8 mm
STRIPPING LENGTH (MAIN CABLE)	8 mm
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (0.5 - 1.5) mm², Main cables 1 x (0.5 - 1.5) mm², Control circuit cables 1 x (0.5 - 1.5) mm², Main cables
TERMINAL CAPACITY (SOLID)	1 x (0.75 - 2.5) mm², Main cables 1 x (0.75 - 2.5) mm², Control circuit cables 2 x (0.75 - 2.5) mm², Control circuit cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 14, Main cables 2 x (18 - 12), Control circuit cables

Resources

CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-tripping-ze-overload-relay-characteristic-curve.eps eaton-tripping-ze-overload-relay-characteristic-curve-005.eps
DECLARATIONS OF CONFORMITY	eaton-thermal-overload-relay-declaration-of-conformity-uk251271en.pdf eaton-thermal-overload-relay-declaration-of-conformity-eu250788en.pdf
DRAWINGS	eaton-tripping-devices-overload-relay-ze-overload-relay-dimensions.eps eaton-tripping-devices-ze-overload-relay-dimensions.eps
ECAD MODEL	ETN.ZE-1,0
INSTALLATION INSTRUCTIONS	IL03407007Z
MANUALS AND USER GUIDES	eaton-motor-protective-relay-ze-overload-monitoring-exe-manual-mn03407003z-de-de-en-us.pdf
MCAD MODEL	DA-CS-ze
WIRING DIAGRAMS	eaton-tripping-devices-overload-relay-zb-overload-relay-wiring-diagram.eps eaton-general-release-zeb-overload-relay-wiring-diagram.eps

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.