Specifications







Eaton 178769

Eaton XN-322 Field potential distributor module, 18 channels, GND

General specifications	
PRODUCT NAME	Eaton XN-322 Power distributor
CATALOG NUMBER	178769
MODEL CODE	XN-322-18PD-M
EAN	7640130098336
PRODUCT LENGTH/DEPTH	104.2 mm
PRODUCT HEIGHT	16.8 mm
PRODUCT WIDTH	80.3 mm
PRODUCT WEIGHT	0.055 kg
CERTIFICATIONS	UL508 CE EN 61131-2 EN 61000-6-2 EN 61000-6-4 cULus UL File No.: E135462 CSA-C22.2 No. 142-M

Powering Business Worldwide

Ambient conditions, mechanical

HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	1 m
MOUNTING POSITION	Horizontal
SHOCK RESISTANCE	15 g, Mechanical, Half-sinusoidal shock 11 ms, 18 Impacts
VIBRATION RESISTANCE	5 - 8.4 / 8.4 -150 Hz, 3,5 mm / 1 g

Climatic environmental conditions

AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT OPERATING TEMPERATURE - MIN	0 °C
AMBIENT STORAGE TEMPERATURE - MIN	-20 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-3 Dry heat to IEC 60068-2-2
ENVIRONMENTAL CONDITIONS	Condensation: prevent with appropriate measures
RELATIVE HUMIDITY	0 - 95 % (non-condensing)

Communication

CONNECTION TYPE	Push-in spring-cage terminal (plug-in connection), Connection design in TOP direction

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV)	Meets the product standard's requirements.

RADIATION	
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Electrical rating

RATED OPERATIONAL CURRENT (IE) - MAX	8 A
RATED OPERATIONAL VOLTAGE	160 V (terminations)
SUPPLY VOLTAGE AT DC - MAX	30 VDC
SUPPLY VOLTAGE AT DC - MIN	18 VDC

Electro magnetic compatibility

AIR DISCHARGE	4 kV (Contact discharge) 8 kV (Air discharge)
BURST IMPULSE	2 kV, Supply cable 1 kV, Signal cable
ELECTROMAGNETIC FIELDS	10 V/m at 0.08 - 1.0 GHz (according to IEC EN 61000-4-3) 1 V/m at 2 - 2.7 GHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
EMITTED INTERFERENCE	47 dB (at 230 - 1000 MHz, Class A, radiated, high frequency) 40 dB (at 30 - 230 MHz, Class A, radiated, high frequency)
RADIATED RFI	10 V
SURGE RATING	0.5/0.5 kV, Supply cable, balanced/unbalanced), EMC 1 kV, Signal cable, unbalanced, EMC
VOLTAGE DIPS	Voltage dips: 10 ms/Voltage fluctuations: Yes

Features & functions

ELECTRIC CONNECTION TYPE	Plug-in connection
FEATURES	Fieldbus connection over separate bus coupler possible Fieldbus connection over separate bus coupler possible

General information

DEGREE OF PROTECTION	IP20
MOUNTING METHOD	Rail mounting possible
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	XN-322 power supply module
TYPE	XN300 power supply module
USED WITH	XN300 XN-312-...
VOLTAGE TYPE	DC

Input/Output

LOAD CURRENT	Not specified by plug manufacturer

Safety

EXPLOSION SAFETY CATEGORY FOR DUST	None
EXPLOSION SAFETY	None

Terminal capacities

GAUGE PIN	A1 (according to IEC/EN 60947-1)
INSULATING MATERIAL GROUP	I
STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY	24 - 16 AWG 0.25 - 1.5 mm², with ferrules with plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 0.2 - 1.5 mm², flexible without ferrule, H07V-K 0.2 - 1.5 mm², solid, H07V-U 0.25 - 1.5 mm², with ferrules without plastic collar according to DIN 46228-1 (ferrules crimped gas-tight)

CATEGORY FOR GAS	

Resources

BROCHURES	Slice card modular I/O system for the machine building industry XN300 - brochure eaton-xc300-modular-plc-brochure-br050008en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-input-module-declaration-of-conformity-uk251198en.pdf eaton-input-module-declaration-of-conformity-eu250715en.pdf
DRAWINGS	eaton-modular-plc-xn-input-module-dimensions.eps eaton-modular-plc-xn-input-module-3d-drawing-006.eps eaton-modular-plc-xn-power-distributor-3d-drawing.eps eaton-general-xv-touch-panel-symbol.eps
ECAD MODEL	DA-CE-ETN.XN-322-18PD-M
INSTALLATION INSTRUCTIONS	IL050025ZU IL050017ZU
MANUALS AND USER GUIDES	eaton-xn300-slice-modules-mn050002-en-us.pdf eaton-xn-312-gw-can-canopen-gateway-mn050003-en-us.pdf
MCAD MODEL	eaton-power-supply-modules-mcad-drawings-xn-322-18pd-m.dwg eaton-power-supply-modules-mcad-3d-models-xn-322-18pd-m.stp
MULTIMEDIA	System solutions based on EtherCAT XC100, XC200, XC300 – Eaton's modular PLC ranges

PRODUCT NOTIFICATIONS	eaton-xn-322-i-o-series-end-user-license-agreement-mz050026-en-us.pdf eaton-xn-322-i-o-series-product-cybersecurity-guideline-mz050024-en-us.pdf

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.