Specifications



Photo is representative





Eaton 171379

Eaton Moeller® series SL4 Acoustic module, 24 V, continuous or pulsed tone

General specifications	
PRODUCT NAME	Eaton Moeller® series SL4 Acoustic module
CATALOG NUMBER	171379
MODEL CODE	SL4-AP24
EAN	4015081679089
PRODUCT LENGTH/DEPTH	43 mm
PRODUCT HEIGHT	72 mm
PRODUCT WIDTH	43 mm
PRODUCT WEIGHT	0.043 kg
CERTIFICATIONS	UL report applies to both US and Canada CSA-C22.2 No. 94-91 IEC/EN 60529 UL File No.: E29184 Certified by UL for use in Canada CSA Class No.: NKCR7 CSA-C22.2 No. 14-10 IEC/EN 60947-5-1 UL UL 508 UL Category Control No.: NKCR CE

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Electrical rating

LEAKAGE CURRENT	0.003 A
RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL CURRENT (IE) - MAX	39 mA
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	24 V
RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	24 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	24 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	24 V

Features & functions

COLOR	Black
FUNCTIONS	Continuous tone/pulse tone

General information

ALARM TYPE	Pulsed tone Continuous tone Internal sound setting, 1 pole DIP 2 types of sound Tone adjustable
CONNECTION TO SMARTWIRE-DT	No
CURRENT CONSUMPTION	0.039 A, at 24 V AC/DC
DEGREE OF PROTECTION	NEMA 13 IP66
FREQUENCY RATING	4000 Hz
LOUDNESS	80 dB
MATERIAL	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
MOUNTING POSITION	As required Place only at the highest position on a pole
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	SL signal towers
RADIATION ANGLE	360 °
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
TYPE	Acoustic module
VOLTAGE TYPE	AC/DC

Resources

BROCHURES	SL4, SL7, SLC Stack light overview brochure BR047017
CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf eaton-rmq-titan-brochure-br047004en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf
DRAWINGS	eaton-operating-sl4-acoustic-module-dimensions.eps eaton-operating-sl7-acoustic-module-symbol.eps eaton-operating-sl7-acoustic-module-symbol-002.eps eaton-operating-sl4-acoustic-module-3d-drawing.eps eaton-operating-button-sl7-base-module-symbol.eps
ECAD MODEL	ETN.SL4-AP24
INSTALLATION INSTRUCTIONS	IL047001ZU
INSTALLATION VIDEOS	Signal towers SL4 and SL7
MCAD MODEL	eaton-acoustic-modules-mcad-drawings-sl4-ap.dwg DA-CS-sl4_ap

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.