Specifications



Eaton 171303

Eaton Moeller® series SL4 Base module, for vertical mounting on one sides

General specifications	
PRODUCT NAME	Eaton Moeller® series SL4 Base module
CATALOG NUMBER	171303
MODEL CODE	SL4-PIB-FW
EAN	4015081678457
PRODUCT LENGTH/DEPTH	56 mm
PRODUCT HEIGHT	94 mm
PRODUCT WIDTH	66 mm
PRODUCT WEIGHT	0.067 kg
CERTIFICATIONS	UL report applies to both US and Canada CSA Class No.: NKCR7 CSA-C22.2 No. 14-10 IEC/EN 60947-5-1 IEC/EN 60529 UL File No.: E29184 CE UL Certified by UL for use in Canada UL 508 UL Category Control No.: NKCR CSA-C22.2 No. 94-91

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Electrical rating

RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL VOLTAGE	24 V AC/DC ± 10 % 110/120 V AC ± 10 % 230/240 V AC ± 10 %

Features & functions

COLOR	Other
FITTED WITH:	Cover Bracket
NUMBER OF MODULES	Max. 10 (with base for mounting on both sides) Max. 5 (with standard base) Max. 5

General information

CONNECTION TO SMARTWIRE-DT	No
DEGREE OF PROTECTION	NEMA 13 NEMA 4X IP66 NEMA 4
MOUNTING METHOD	Bracket Floor Vertical
MOUNTING POSITION	As required
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	SL signal towers
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
TYPE	Base module

Terminal capacities

TERMINAL CAPACITY (AWG)	24 - 16
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE AND PLASTIC COLLAR)	0.25 - 0.75 mm²
TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE)	0.25 - 1.5 mm²
TERMINAL CAPACITY (SOLID/FLEXIBLE)	0.2 - 1.5 mm²

Resources

BROCHURES	SL4, SL7, SLC Stack light overview brochure BR047017
CATALOGUES	eaton-rmq-titan-brochure-br047004en-en-us.pdf eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf
DRAWINGS	eaton-operating-devices-dimensions-028.eps eaton-operating-button-sl7-base-module-symbol.eps

	1160DRW-305
ECAD MODEL	DA-CE-ETN.SL4-PIB-FW
INSTALLATION INSTRUCTIONS	IL047001ZU IL047002ZU
INSTALLATION VIDEOS	Signal towers SL4 and SL7
MCAD MODEL	DA-CS-sl4_pib_fw eaton-base-modules-mcad-drawings-sl4-pib-fw.dwg

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.