# Specifications



Photo is representative





## Eaton 171388

Eaton Moeller® series SL7 Flashing light module, yellow, LED, 24 V

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton Moeller® series SL7 Flashing light module |
| **CATALOG NUMBER** | 171388 |
| **MODEL CODE** | SL7-BL24-Y |
| **EAN** | 4015081679232 |
| **PRODUCT LENGTH/DEPTH** | 73 mm |
| **PRODUCT HEIGHT** | 73 mm |
| **PRODUCT WIDTH** | 73 mm |
| **PRODUCT WEIGHT** | 0.08 kg |
| **CERTIFICATIONS** | UL 508<br>UL report applies to both US and Canada<br>UL<br>UL Category Control No.: NKCR<br>CSA-C22.2 No. 94-91<br>IEC/EN 60529<br>IEC/EN 60947-5-1<br>Certified by UL for use in Canada<br>UL File No.: E29184<br>CSA Class No.: NKCR7<br>CE<br>CSA-C22.2 No. 14-10 |

## Climatic environmental conditions

| | |
|---|---|
| **AMBIENT OPERATING TEMPERATURE - MAX** | 60 °C |
| **AMBIENT OPERATING TEMPERATURE - MIN** | -30 °C |
| **CLIMATIC PROOFING** | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |

## Electrical rating

| | |
|---|---|
| **LEAKAGE CURRENT** | 0.003 A |
| **RATED INSULATION VOLTAGE (UI)** | 250 V |
| **RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX** | 24 V |
| **RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN** | 24 V |
| **RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX** | 24 V |
| **RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN** | 24 V |

## Features & functions

| | |
|---|---|
| **COLOR** | Yellow |
| **ENCLOSURE COLOR** | Black |
| **FUNCTIONS** | Blinker light |
| **LIGHT MODULES** | LED |
| **NUMBER OF MODULES** | Max. 10 (with base for mounting on both sides)<br>Max. 5 (with standard base) |

## General information

| | |
|---|---|
| **CONNECTION TO SMARTWIRE-DT** | No |
| **CURRENT CONSUMPTION** | 50 mA at 24 V AC/DC |
| **DEGREE OF PROTECTION** | IP66<br>NEMA 13 |
| **FLASHING FREQUENCY** | 2 Hz |
| **LIFESPAN, ELECTRICAL** | 100,000 h |
| **LIGHT TYPE** | Flashing light |
| **MATERIAL** | Cap: Polycarbonate (PC)<br>Enclosure: Polycarbonate (PC) |
| **MOUNTING POSITION** | As required |
| **OVERVOLTAGE CATEGORY** | III |
| **POLLUTION DEGREE** | 3 |
| **PRODUCT CATEGORY** | SL signal towers |
| **RADIATION ANGLE** | 360 ° |
| **RATED IMPULSE WITHSTAND VOLTAGE (UIMP)** | 4000 V AC |
| **SHOCK RESISTANCE** | 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27 |
| **TYPE** | Flashing light module |
| **VOLTAGE TYPE** | AC/DC |

## Resources

| | |
|---|---|
| **BROCHURES** | SL4, SL7, SLC Stack light overview brochure BR047017 |
| **CATALOGUES** | eaton-rmq-titan-brochure-br047004en-en-us.pdf<br><br>eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf |
| **DECLARATIONS OF CONFORMITY** | eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf<br><br>eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf |
| **DRAWINGS** | eaton-operating-dimensions-005.eps<br><br>eaton-operating-button-sl7-continuous-light-symbol-004.eps<br><br>eaton-operating-sl7-flashing-light-symbol.eps |
| **ECAD MODEL** | ETN.171388.edz |
| **INSTALLATION INSTRUCTIONS** | IL047004ZU |
| **INSTALLATION VIDEOS** | Signal towers SL4 and SL7 |
| **MCAD MODEL** | DA-CS-sl7_bfl7 |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.