# Specifications



**Photo is representative**

## Eaton 216701

Eaton Moeller® series M22 Double actuator pushbutton, RMQ-Titan, Actuators and indicator lights non-flush, momentary, White lens, green, red, inscribed, Bezel: black

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton Moeller® series M22 double actuator pushbutton |
| **CATALOG NUMBER** | 216701 |
| **MODEL CODE** | M22S-DDL-GR-X1/X0 |
| **EAN** | 4015082167011 |
| **PRODUCT LENGTH/DEPTH** | 30 mm |
| **PRODUCT HEIGHT** | 55 mm |
| **PRODUCT WIDTH** | 30 mm |
| **PRODUCT WEIGHT** | 0.015 kg |
| **CERTIFICATIONS** | CSA Class No.: 3211-03<br>IEC/EN 60947<br>IEC/EN 60947-5<br>CE<br>CSA-C22.2 No. 94-91<br>UL<br>UL File No.: E29184<br>CSA-C22.2 No. 14-05<br>UL Category Control No.: NKCR<br>UL 508<br>CSA<br>CSA File No.: 012528<br>VDE 0660<br>DNV<br>GL<br>LR |

## Actuator

| | |
|---|---|
| **ACTUATING FORCE** | 5 N |
| **ACTUATOR COLOR** | Green, red |
| **ACTUATOR FUNCTION** | Spring-return<br>Momentary |
| **BEZEL COLOR** | Black |
| **BEZEL MATERIAL** | Plastic |
| **DESIGN** | Non-Flush<br>Classical |
| **FEATURES** | Labelled |
| **FITTED WITH:** | Front ring |
| **INSCRIPTION** | Inscribed |
| **LENS COLOR** | White |
| **LENS TYPE** | Oval |
| **NUMBER OF COMMAND POSITIONS** | 2 |

## Communication

| | |
|---|---|
| **CONNECTION TO SMARTWIRE-DT** | With SWD-RMQ connections<br>Yes |

## Climatic environmental conditions

| | |
|---|---|
| **AMBIENT OPERATING TEMPERATURE - MAX** | 70 °C |
| **AMBIENT STORAGE TEMPERATURE - MAX** | 80 °C |
| **AMBIENT OPERATING TEMPERATURE - MIN** | -25 °C |
| **AMBIENT STORAGE TEMPERATURE - MIN** | 40 °C |
| **CLIMATIC PROOFING** | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78 |

## Design verification

| | |
|---|---|
| **10.10 TEMPERATURE RISE** | Not applicable. |
| **10.11 SHORT-CIRCUIT RATING** | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| **10.12 ELECTROMAGNETIC COMPATIBILITY** | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| **10.13 MECHANICAL FUNCTION** | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| **10.2.2 CORROSION RESISTANCE** | Meets the product standard's requirements. |
| **10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES** | Meets the product standard's requirements. |
| **10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT** | Meets the product standard's requirements. |
| **10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS** | Meets the product standard's requirements. |
| **10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION** | Please enquire |
| **10.2.5 LIFTING** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.2.6 MECHANICAL IMPACT** | Does not apply, since the entire switchgear needs to be evaluated. |

| | |
|---|---|
| **10.2.7 INSCRIPTIONS** | Meets the product standard's requirements. |
| **10.3 DEGREE OF PROTECTION OF ASSEMBLIES** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.4 CLEARANCES AND CREEPAGE DISTANCES** | Meets the product standard's requirements. |
| **10.5 PROTECTION AGAINST ELECTRIC SHOCK** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS** | Is the panel builder's responsibility. |
| **10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS** | Is the panel builder's responsibility. |
| **10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH** | Is the panel builder's responsibility. |
| **10.9.3 IMPULSE WITHSTAND VOLTAGE** | Is the panel builder's responsibility. |
| **10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL** | Is the panel builder's responsibility. |
| **EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID** | 0 W |
| **HEAT DISSIPATION CAPACITY PDISS** | 0 W |
| **HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID** | 0 W |
| **RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)** | 0 A |
| **STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS** | 0 W |

## General information

| | |
|---|---|
| **DEGREE OF PROTECTION** | NEMA 13<br>NEMA 12<br>NEMA 3R<br>IP66<br>NEMA 4X |
| **DEGREE OF PROTECTION (FRONT SIDE)** | IP66<br>NEMA 4X |
| **LIFESPAN, MECHANICAL** | 200,000 Operations |
| **MOUNTING POSITION** | As required |
| **OPENING DIAMETER** | 22.5 mm |
| **OPERATING FREQUENCY** | 3600 Operations/h |
| **PRODUCT CATEGORY** | RMQ-Titan |
| **SIZE** | Front dimensions: 29,7 x 54,7 mm |
| **SUITABLE FOR** | Illumination |
| **TYPE** | Double actuator |

## Resources

| | |
|---|---|
| **CATALOGUES** | eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf<br><br>eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf |
| **DECLARATIONS OF CONFORMITY** | eaton-double-actuator-pushbutton-declaration-of-conformity-eu251536en.pdf |
| **DRAWINGS** | eaton-operating-pushbutton-m22-double-actuator-pushbutton-dimensions.eps<br><br>eaton-operating-pushbutton-m22-double-actuator-pushbutton-dimensions-002.eps<br><br>eaton-operating-button-m22-double-actuator-pushbutton-symbol-002.eps<br><br>eaton-general-approval-m22-symbol.eps<br><br>eaton-general-m22-standards.eps<br><br>eaton-general-m22-symbol.eps |
| **ECAD MODEL** | ETN.216701.edz |
| **INSTALLATION INSTRUCTIONS** | IL04716002Z |
| **MCAD MODEL** | DA-CS-doppeldrucktaste_normal_normal |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.