Specifications



Eaton 207440

Eaton Moeller® series CI-K Insulated enclosure, HxWxD=240x160x161mm, for T5B-4

General specifications	
PRODUCT NAME	Eaton Moeller® series CI-K Insulated enclosure
CATALOG NUMBER	207440
MODEL CODE	CI-K4-T5B-4
EAN	4015082074401
PRODUCT LENGTH/DEPTH	160 mm
PRODUCT HEIGHT	240 mm
PRODUCT WIDTH	160 mm
PRODUCT WEIGHT	0.88 kg
CERTIFICATIONS	CE UL 508 UL UL Category Control No.: MITW2 UL File No.: E54120 CSA File No.: 012528 IEC/EN 60947-3 CSA-C22.2 No. 14-05 CSA Class No.: 3211-07 CSA-C22.2 No. 94 CSA
CATALOG NOTES	1 contact unit = 2 contacts

Product specifications

USED WITH	T5B-…/Z with an additional PE clamp
TYPE	Insulated enclosure
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.

Resources

BROCHURES	Brochure - CI-K small enclosures
CATALOGUES	P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN
DECLARATIONS OF CONFORMITY	eaton-insulated-enclosure-declaration-of-conformity-uk251038en.pdf eaton-insulated-enclosure-declaration-of-conformity-eu250555en.pdf
DRAWINGS	eaton-rotary-switches-ci-k-insulated-enclosure-dimensions-002.eps eaton-rotary-switches-enclosure-ci-k-insulated-enclosure-3d-drawing.eps
ECAD MODEL	DA-CE-ETN.CI-K4-T5B-4
INSTALLATION INSTRUCTIONS	IL03801009Z
MCAD MODEL	DA-CS-bauform14_n

10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	Additional terminal Metric knockouts
ENCLOSURE MATERIAL	Plastic
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	29.5 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
DEGREE OF PROTECTION	IP65 NEMA 12
MODEL	Surface mounting
RADIATED HEAT DISSIPATION WITH SEPARATE MOUNTING	29.5 W (at an ambient temperature of 20 °C)

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.