Specifications



Eaton 144123

Eaton Moeller® series SOL30 Safety Fireman's switch, 25A, MV, UA 230V50Hz

General specifications	
PRODUCT NAME	Eaton Moeller® series SOL30 Safety Fireman's switch
CATALOG NUMBER	144123
MODEL CODE	SOL30-SAFETY/2MV-U(230V50HZ)
EAN	4015081406333
PRODUCT LENGTH/DEPTH	224 mm
PRODUCT HEIGHT	130 mm
PRODUCT WIDTH	100 mm
PRODUCT WEIGHT	1.006 kg
CERTIFICATIONS	IEC/EN 60 947-3

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Electrical rating

RATED OPERATIONAL CURRENT (IE) AT DC-21A	30 A
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V
RATED UNINTERRUPTED CURRENT (IU)	32 A
RESISTANCE	7 mΩ (internal)

General information

APPLICATION	• Residential buildings • Utility buildings
CONNECTION TYPE	M12, Outputs M12, Inputs
DEGREE OF PROTECTION	NEMA Other
DEGREE OF PROTECTION (FRONT SIDE)	IP65
LIFESPAN, ELECTRICAL	1,500 Operations
LIFESPAN, MECHANICAL	100,000 Operations
OPERATING FREQUENCY	120 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	• Fireman's Switch • Switchgear for photovoltaic systems
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	8000 V
SUITABLE FOR	Ground mounting Floor mounting
UTILIZATION CATEGORY	DC-21 A

Contacts

NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	1
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0

Features & functions

ACTUATOR COLOR	Black
ACTUATOR TYPE	Toggle
FEATURES	Version as maintenance-/service switch
FITTED WITH:	Voltage release optional
LOCKING FACILITY	Lockable in the 0 (Off) position (with padlock)
NUMBER OF POLES	Two-pole

Short-circuit rating

RATED SHORT-CIRCUIT MAKING CAPACITY (ICM)	0.3 kA (up to 440 V, 50/60 Hz)
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	0.36 kA

Resources

CHARACTERISTIC CURVE	eaton-manual-motor-starters-sol30-fireman's-switch-3d-drawing.eps eaton-manual-motor-starters-switch-sol30-fireman's-switch-dimensions.eps eaton-motorstarters-undervoltage-sol30-fireman's-switch-characteristic-curve.eps eaton-manual-motor-starters-sol30-fireman's-switch-3d-drawing-008.eps
DECLARATIONS OF CONFORMITY	eaton-fireman-s-switch-declaration-of-conformity-eu250782en.pdf eaton-fireman-s-switch-declaration-of-conformity-uk251265en.pdf
ECAD MODEL	DA-CE-ETN.SOL30-SAFETY_2MV-U(230V50HZ)
INSTALLATION INSTRUCTIONS	eaton-fireman-switch-sol30-safety-il03801002z.pdf

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.