Specifications







Eaton 121723

Eaton Moeller® series PKE Trip block, 0.3 - 1.2 A, Motor protection, Connection to SmartWire-DT: no, For use with: PKE12 basic device

General specifications	
PRODUCT NAME	Eaton Moeller® series PKE Trip block
CATALOG NUMBER	121723
MODEL CODE	PKE-XTU-1,2
EAN	4015081195336
PRODUCT LENGTH/DEPTH	41.6 mm
PRODUCT HEIGHT	64.2 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.09 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	IEC 60947-4-1 CSA Std. C22.2 No. 14-10 UL 508 EN 60947-4-1 VDE IEC/EN 60947 CSA CSA Class No.: 3211-05 CSA-C22.2 No. 14-10 UL Category Control No.: NLRV CE UL File No.: E36332 CSA File No.: 165628 UL IEC/EN 60947-4-1 VDE 0660
CATALOG NOTES	This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures.

Ambient conditions, mechanical

SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Climatic environmental conditions

ALTITUDE	Max. 2000 m
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Communication

CONNECTION TO SMARTWIRE-DT	No

Contacts

NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.

Electrical rating

RATED FREQUENCY - MAX	60 Hz
RATED FREQUENCY - MIN	50 Hz
RATED OPERATIONAL CURRENT (IE)	1.2 A
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V
RATED UNINTERRUPTED CURRENT (IU)	1.2 A
SUPPLY VOLTAGE AT AC, 50 HZ - MAX	690 V
SUPPLY VOLTAGE AT AC, 50 HZ - MIN	690 V

10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0.3 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.1 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	1.2 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Features & functions

FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
FUNCTIONS	Motor protection Overload release Motor protection for heavy starting duty
NUMBER OF POLES	Three-pole

General information

CURRENT FLOW TIMES - MIN	Note: Going below the minimum current flow time can cause overheating of the load (motor). 500 (Class 5) AC-4 cycle operation, Main conducting paths 900 (Class 15) AC-4 cycle operation, Main conducting paths 1000 (Class 20) AC-4 cycle operation, Main conducting paths For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods. 700 (Class 10) AC-4 cycle operation, Main conducting paths
CUT-OUT PERIODS - MIN	≤ 500 ms, main conducting paths, AC-4 cycle operation
DEGREE OF PROTECTION	Terminals: IP00 Device: IP20
OPERATING FREQUENCY	60 Operations/h
OVERLOAD RELEASE CURRENT SETTING - MAX	1.2 A
OVERLOAD RELEASE CURRENT SETTING - MIN	0.3 A
OVERVOLTAGE	III

CATEGORY	
POLLUTION DEGREE	3
PRODUCT CATEGORY	Accessories
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
TEMPERATURE COMPENSATION	-5 - 40 °C to IEC/EN 60947, VDE 0660 -25 - 55 °C, Operating range
USED WITH	PKE12 basic device
VOLTAGE TYPE	Self powered

Magnet system

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	0 V

Short-circuit rating

SHORT-CIRCUIT RELEASE	± 20% tolerance, Trip blocks Trip block fixed 15.5 x Ir Delayed approx. 60 ms, Trip blocks

Switching capacity

SWITCHING CAPACITY AT AC-3 (UP TO 690 V)	1.2 A

Resources

BROCHURES	eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf eaton-motor-protective-circuit-breaker-pke-and-communication-modul-pke-brochure-w12107613en-en-us.pdf
CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-manual-motor-starters-pke65-characteristic-curve-005.eps
DECLARATIONS OF CONFORMITY	eaton-system-protective-circuit-breaker-declaration-of-conformity-eu250694en.pdf

	eaton-system-protective-circuit-breaker-declaration-of-conformity-uk251177en.pdf
DRAWINGS	eaton-general-ie-ready-dilm-contactor-standards.eps eaton-manual-motor-starters-mounting-3d-drawing.eps eaton-manual-motor-starters-pke-trip-block-3d-drawing-002.eps
ECAD MODEL	ETN.121723.edz
INSTALLATION INSTRUCTIONS	eaton-trip-block-pke-xtu-for-pke12-pke32-il034011zu.pdf
INSTALLATION VIDEOS	WIN-WIN with push-in technology Video Motor Protective Circuit Breaker PKE
MANUALS AND USER GUIDES	eaton-motor-protection-pke12-32-65-mn03402004z-de-de-en-us.pdf
MCAD MODEL	eaton-accessories-mcad-drawings-pke-xtu12.dwg DA-CS-pke_xtu12
SALES NOTES	eaton-pke-modbus-rtu-modul-flyer-fl034008en-en-us.pdf

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.