Specifications





Eaton 106132

Eaton Moeller® series PKZ0 Door coupling handle, EN60204

General specifications	
PRODUCT NAME	Eaton Moeller® series PKZ0 Accessory Door coupling handle
CATALOG NUMBER	106132
MODEL CODE	PKZ0-XH
EAN	4015081059027
PRODUCT LENGTH/DEPTH	235 mm
PRODUCT HEIGHT	66 mm
PRODUCT WIDTH	64 mm
PRODUCT WEIGHT	0.16 kg
CERTIFICATIONS	IEC/EN 60947-4-1 CE UL Category Control No.: NLRV CSA-C22.2 No. 14 CSA File No.: 165628 UL CSA UL File No.: E36332 UL 508 CSA Class No.: 3211-05
CATALOG NOTES	Cannot be used in combination with VHI20-PKZ0.

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C

Design verification

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL	Is the panel builder's

ELECTRICAL CIRCUITS AND CONNECTIONS	responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W

Features & functions

COLOR	Black
FEATURES	Lockable
FITTED WITH:	Extension shaft ON/OFF switch position and “+” (tripped), lockable 3 padlocks, 4 - 8 mm hasp thickness

General information

DEGREE OF PROTECTION	IP65 NEMA 4X, 12
PRODUCT CATEGORY	Accessories
SUITABLE AS	Main switch to IEC/EN 60204
USED WITH	PKZ0-XH

Resources

BROCHURES	eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf eaton-push-in-technology-product-overview-brochure-br034012-en-us.pdf
CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
DRAWINGS	eaton-manual-motor-starters-pkz0-accessory-dimensions-003.eps
ECAD MODEL	ETN.106132.edz
INSTALLATION INSTRUCTIONS	eaton-door-coupling-rotary-handle-pkz0-pke-il03402018z.pdf
INSTALLATION VIDEOS	WIN-WIN with push-in technology
MCAD MODEL	DA-CS-pkz0_x_r_h eaton-accessories-mcad-drawings-pkz0-x-r-h.dwg
SALES NOTES	eaton-link-module-for-motor-starters-pkz-flyer-fl034003en-en-us.pdf

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.