Specifications



Photo is representative

Eaton 260170

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, lockable, size 3

General specifications	
PRODUCT NAME	Eaton Moeller series NZM operating element
CATALOG NUMBER	260170
MODEL CODE	NZM3-XTVD
EAN	4015082601706
PRODUCT LENGTH/DEPTH	100 mm
PRODUCT HEIGHT	230 mm
PRODUCT WIDTH	140 mm
PRODUCT WEIGHT	1.373 kg
COMPLIANCES	IEC UL/CSA RoHS conform
CERTIFICATIONS	UL (Category Control Number DIHS) CSA-C22.2 No. 5-09 CSA (Class No. 1437-01) CE marking UL listed IEC60947 UL (File No. E140305) CSA (File No. 22086) CSA certified UL489

Delivery program

FEATURES	Lockable Standard: black / gray
FITTED WITH:	Padlock
FRAME	NZM3
SPECIAL FEATURES	• Door coupling rotary handle for operating the switch through a closed control panel door • External warning plate/designation label can be clipped on. • Complete including rotary drive and coupling parts • Extension shaft additionally required.
SUITABLE FOR	Switch disconnector Power circuit breaker
TYPE	• Accessory • Door coupling rotary handle
USED WITH	NZM3(-4), PN3(-4), N(S)3(-4)

Design verification as per IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.

10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - mechanical

COLOR	Black
COVER/DOOR TYPE	Door can be opened in OFF Door interlock not defeated in the locked OFF and ON positions Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door interlock can be modified in the unlocked ON position
DEGREE OF PROTECTION / NEMA ENCLOSURE TYPE	IP66 4X. 12
LOCK NUMBER	Single lockable
LOCKING FACILITY	Lockable on the 0 position on the handle using up to 3 padlocks With door interlock
SPECIAL FEATURES	• Door coupling rotary handle for operating the switch through a closed control panel door • External warning plate/designation label can be clipped on. • Complete including rotary drive and coupling parts • Extension shaft additionally required.

Resources

BROCHURES	eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf eaton-digital-nzm-brochure-br013003en-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
DRAWINGS	eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-003.eps eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-006.eps eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-005.eps
INSTALLATION INSTRUCTIONS	IL01208007Z
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM The new digital NZM Range
MCAD MODEL	eaton-handle-mechanisms-mcad-3d-models-nzm3-xtvd-60.stp eaton-handle-mechanisms-mcad-drawings-nzm3-xtvd.dwg
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.