Specifications



Photo is representative

Eaton 260197

Eaton Moeller series NZM - Molded Case Circuit Breaker. Insulating surround, size 2

General specifications

PRODUCT NAME	Eaton Moeller series NZM operating element accessory
CATALOG NUMBER	260197
MODEL CODE	NZM2-XBR
EAN	4015082601973
PRODUCT LENGTH/DEPTH	17.5 mm
PRODUCT HEIGHT	132 mm
PRODUCT WIDTH	158.5 mm
PRODUCT WEIGHT	0.064 kg
COMPLIANCES	UL/CSA IEC RoHS conform
CERTIFICATIONS	UL listed CSA (File No. 22086) CSA (Class No. 1437-01) UL489 CSA-C22.2 No. 5-09 CSA certified IEC60947 UL (File No. E140305) UL (Category Control Number DIHS) CE marking

Delivery program

FRAME	NZM2
SPECIAL FEATURES	For toggle levers, rotary handles with rotary drive and remote operators
TYPE	• Accessory • Insulating surrounds
USED WITH	PN2(-4) N(S)2(-4) NZM2(-4)

Design verification as per IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.

10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - mechanical

COLOR	Black
DEGREE OF PROTECTION	IP40
MATERIAL	Plastic
SPECIAL FEATURES	For toggle levers, rotary handles with rotary drive and remote operators

Resources

BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
DRAWINGS	eaton-circuit-breaker-insulating-nzm-mccb-dimensions-005.eps eaton-circuit-breaker-insulating-nzm-mccb-3d-drawing-005.eps
INSTALLATION INSTRUCTIONS	eaton-nzm-insulating-surround-size1-2-il01219011z.pdf
INSTALLATION VIDEOS	The new digital NZM Range Introduction of the new digital circuit breaker NZM
MCAD MODEL	nzm2_xbr.stp eaton-mccb-terminal-accessories-mcad-drawings-nzm2-xbr.dwg
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.