Specifications





Photo is representative

Eaton 259854

Eaton Moeller series NZM Remote operator, 24-30VDC, for size 3

General specifications	
PRODUCT NAME	Eaton Moeller series NZM remote operator
CATALOG NUMBER	259854
MODEL CODE	NZM3-XR24-30DC
EAN	4015082598549
PRODUCT LENGTH/DEPTH	170 mm
PRODUCT HEIGHT	140 mm
PRODUCT WIDTH	140 mm
PRODUCT WEIGHT	2.8 kg
COMPLIANCES	UL/CSA IEC RoHS conform
CERTIFICATIONS	UL (Category Control Number DIHS) IEC60947 CE marking UL (File No. E140305) UL listed CSA (File No. 22086) CSA-C22.2 No. 5-09 CSA certified CSA (Class No. 1437-01) UL489

Delivery program

FRAME	NZM3
NUMBER OF POLES	Three-pole/Four-pole
SPECIAL FEATURES	• Cannot be combined with switch-disconnector PN... • M22-CK11(20/02) dual auxiliary switch cannot be combined with NZM3-XR… remote operator
TYPE	Remote operator, can be synchronized
USED WITH	N(S)3(-4) NZM3(-4)

Design verification as per IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.

10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

BREAKING TIME	1000 ms
CLOSING DELAY	80 ms
NUMBER OF OPERATIONS PER HOUR - MAX	60
OPERATING VOLTAGE - MAX	1.1 x Us
OPERATING VOLTAGE - MIN	0.85 x Us
POWER CONSUMPTION	250 W (24 - 30 V DC)
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	30 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	24 V
SIGNAL DURATION OF REMOTE OPERATOR AT SWITCH OFF - MIN	250 ms
SIGNAL DURATION OF REMOTE OPERATOR AT SWITCH ON - MIN	30 ms
VOLTAGE RATING	24 - 30 V DC
VOLTAGE TOLERANCE - MAX	1.1
VOLTAGE TOLERANCE - MIN	0.85
VOLTAGE TYPE	DC

Technical data - mechanical

LIFESPAN, MECHANICAL	15000 operations
SPECIAL FEATURES	• Cannot be combined with switch-disconnector PN... • M22-CK11(20/02) dual auxiliary switch cannot be combined with NZM3-XR… remote operator
SWITCH DRIVE TYPE	Motor drive

Technical data - mechanical - terminals

TERMINAL CAPACITY (SOLID/FLEXIBLE CONDUCTOR)	0.75 mm² - 2.5 mm² with ferrule 18 - 14 AWG

Resources

BROCHURES	eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf eaton-digital-nzm-brochure-br013003en-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf

DECLARATIONS OF CONFORMITY	eaton-accessories-declaration-of-conformity-eu250142en.pdf eaton-accessories-declaration-of-conformity-uk251456en.pdf
DRAWINGS	eaton-circuit-breaker-remote-operator-nzm-remote-operator-dimensions-004.eps eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps
ECAD MODEL	ETN.259854.edz
INSTALLATION INSTRUCTIONS	eaton-remote-operator-nzm3-xr-il01208006z.pdf
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM The new digital NZM Range
MCAD MODEL	DA-CS-nzm3_xr
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.