Specifications



Eaton 266765

Eaton Moeller series NZM - Molded Case Circuit Breaker. Connection, on rear, 3p, 1 switch side

General specifications	
PRODUCT NAME	Eaton Moeller series NZM connection type
CATALOG NUMBER	266765
MODEL CODE	NZM2-XKR
EAN	4015082667658
PRODUCT LENGTH/DEPTH	140 mm
PRODUCT HEIGHT	35 mm
PRODUCT WIDTH	60 mm
PRODUCT WEIGHT	0.403 kg
COMPLIANCES	IEC RoHS conform

Additional information

MODEL	Other

Delivery program

AMPERAGE RATING	300 A (Cu), 250 A (Al)
FRAME	NZM2
NUMBER OF POLES	Three-pole
SUITABLE FOR	Copper cable lugs Three-pole Aluminum cable lug
TYPE	Terminal
USED WITH	NZM2, PN2, N2

Design verification as per IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.

Technical data - electrical

AMPERAGE RATING	300 A (Cu), 250 A (Al)

10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - mechanical - terminals

TERMINAL CAPACITY (COPPER BUSBAR)	Min. 16 mm x 5 mm Max. 24 mm x 8 mm
TERMINAL CAPACITY (COPPER STRIP)	2 segments of 16 mm x 0.8 mm - 6 segments of 24 mm x 0.5 mm
TERMINAL CAPACITY (STRANDED CABLE)	4 mm² - 185 mm² (1x) 4 mm² - 70 mm² (2x) 10 mm² - 50 mm² (1x) 10 mm² - 50 mm² (2x)

Resources

BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
DRAWINGS	eaton-circuit-breaker-connection-nzm-rear-connection-dimensions-003.eps
INSTALLATION INSTRUCTIONS	eaton-circuit-breakers-nzm2-xkr-o-u-connection-il01219047z.pdf
INSTALLATION VIDEOS	The new digital NZM Range Introduction of the new digital circuit breaker NZM
MCAD MODEL	DA-CS-nzm2_3p_xkr_o_u
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.