Specifications



Eaton 266836

Eaton Moeller series NZM - Molded Case Circuit Breaker. Tunnel terminal, 3p, 1 switch side, size 4

General specifications	
PRODUCT NAME	Eaton Moeller series NZM connection type
CATALOG NUMBER	266836
MODEL CODE	NZM4-XKA
EAN	4015082668365
PRODUCT LENGTH/DEPTH	88 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	159 mm
PRODUCT WEIGHT	2.529 kg
COMPLIANCES	UL/CSA IEC RoHS conform
CERTIFICATIONS	CSA (Class No. 1432-01) CE marking UL listed UL (Category Control Number DIHS) UL (File No. E31593) CSA certified UL489 IEC60947 CSA (File No. 22086) CSA-C22.2 No. 5-09

Additional information

MODEL	Other

Delivery program

AMPERAGE RATING	1400 A
FRAME	NZM4
NUMBER OF POLES	Three-pole
SUITABLE FOR	Three-pole Copper cable
TYPE	• Accessory • Tunnel terminal
USED WITH	NZM4, N(S)4

Design verification as per IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.

Technical data - electrical

AMPERAGE RATING	1400 A

10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - mechanical - terminals

TERMINAL CAPACITY (STRANDED CABLE)	50 mm² - 240 mm² (4x) Max. 500 AWG/kcmil (4x) Max. 500 AWG/kcmil (1x) 50 mm² - 240 mm² (1x)

Resources

BROCHURES	eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf eaton-digital-nzm-brochure-br013003en-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
DRAWINGS	eaton-circuit-breaker-terminals-nzm-tunnel-terminal-dimensions-003.eps eaton-circuit-breaker-terminals-nzm-tunnel-terminal-3d-drawing-005.eps
INSTALLATION INSTRUCTIONS	eaton-circuit-breaker-nzm4-tunnel-flat-conductor-terminal-nzm4-4-xka-xkb-instruction-leaflet-il01210012z.pdf
INSTALLATION VIDEOS	The new digital NZM Range Introduction of the new digital circuit breaker NZM
MCAD MODEL	nzm4_xka.stp
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.