Specifications



Eaton 046374

Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure. Connection terminal, 630A, 3p, flat/round

General specifications	
PRODUCT NAME	Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure
CATALOG NUMBER	046374
MODEL CODE	K2X240/3
EAN	4015080463740
PRODUCT LENGTH/DEPTH	125 mm
PRODUCT HEIGHT	140 mm
PRODUCT WIDTH	190 mm
PRODUCT WEIGHT	5.241 kg
COMPLIANCES	RoHS conform

Additional information

FEATURES	Contact safe
SPECIAL FEATURES	• Conversion kits for strip terminal in cable connection available separately • Terminal covers available separately • Including labels for terminal marking U, V, W - X, Y, Z - L1, L2, L3 - T1, T2, T3 - PE, N, PEN, protective earth (ground) symbol • Relationship of rated operational current →terminal capacity to IEC/EN 60439, VDE 0660 Part 500 or EN 50021 • Outer terminal for round or sectoral conductor, other side for Cu strip
SUITABLE FOR	Useful for stranded conductors
USED WITH	Accessory panel building General switchboard accessory

Delivery program

ACCESSORY/SPARE PART TYPE	Terminations Terminals, 160 – 1000 A
NOMINAL CURRENT	630 A
NUMBER OF POLES	Three-pole
TYPE	• Accessory panel building • General switchboard accessory

Technical data - electrical

RATED INSULATION VOLTAGE (UI)	1000 VAC
RATED OPERATION CURRENT (IE)	630 A

Technical data - mechanical

CONDUCTOR CROSS SECTION, INPUT - MAX	240 mm²
CONDUCTOR CROSS SECTION, INPUT - MIN	70 mm²
CONDUCTOR CROSS SECTION, INPUT AWG - MAX	500 mm²
CONDUCTOR CROSS SECTION, INPUT AWG - MIN	0 mm²
CONDUCTOR CROSS SECTION, OUTPUT - MAX	300 mm²
CONDUCTOR CROSS SECTION, OUTPUT - MIN	70 mm²
CONDUCTOR CROSS SECTION, OUTPUT AWG - MAX	0 mm²
CONDUCTOR CROSS SECTION, OUTPUT AWG - MIN	0 mm²
MOUNTING METHOD	Screw
NUMBER OF CONNECTIONS (LESS THAN 6 MM SQUARED)	0
NUMBER OF CONNECTIONS (LESS THAN AWG 6)	0

NUMBER OF CONNECTIONS (GREATER THAN 25 MM SQUARED)	6
NUMBER OF CONNECTIONS (GREATER THAN 250 KCMIL)	0
NUMBER OF CONNECTIONS (10 MM SQUARED)	0
NUMBER OF CONNECTIONS (16 MM SQUARED)	0
NUMBER OF CONNECTIONS (25 MM SQUARED)	0
NUMBER OF CONNECTIONS (250 KCMIL)	0
NUMBER OF CONNECTIONS (AWG 2)	0
NUMBER OF CONNECTIONS (AWG 4)	0
NUMBER OF CONNECTIONS (AWG 4/0)	0
NUMBER OF CONNECTIONS (AWG 6)	0
NUMBER OF CONNECTIONS (TOTAL)	6
NUMBER OF INPUTS	1
NUMBER OF OUTPUTS	2
TERMINAL CAPACITY (ALUMINUM CABLE)	150 mm² - 240 mm² (1x) 95 mm² - 185 mm² (2x)
TERMINAL CAPACITY (CONDUCTOR)	40 mm x 15 mm
TERMINAL CAPACITY (COPPER BAND)	16 mm x 0.8 mm (10x) for flat strip 21 mm x 1 mm (11x) for flat strip
TERMINAL CAPACITY (COPPER/ALUMINUM CABLE)	150 mm² - 300 mm² (1x) 50 mm² - 240 mm² (2x)
CONNECTION TYPE	Clamp Screwing

Resources

CATALOGUES	eaton-panel-building-accessories-catalog-ca008008en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-xeffect-k-type-terminals-declaration-of-conformity-en-us.pdf eaton-enclosures-declaration-of-conformity-eu250263en.pdf
DRAWINGS	eaton-control-panels-terminals-xeffect-k-type-terminal-3d-drawing.eps
INSTALLATION INSTRUCTIONS	IL015110ZU
MCAD MODEL	eaton-K2X240_3-3d-model.stp
SYSTEM OVERVIEW	eaton-control-panels-terminals-xeffect-k-type-terminal-explosion-drawing-002.eps

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.