# Specifikationer







## Eaton EVMAF316A

Eaton Managed G4 Rack PDU, 0U, 22.5U, IEC-60309 input, 3m cord, 3ph, 11kW, 16A, 415/240V, 24 outlets (12)C13, (12)C39

| Generelle specifikationer | |
|---|---|
| **PRODUCT NAME** | Eaton Rack PDU G4 |
| **CATALOG NUMBER** | EVMAF316A |
| **EAN** | 3553340696985 |
| **PRODUCT LENGTH/DEPTH** | 1000 mm |
| **PRODUCT HEIGHT** | 53 mm |
| **PRODUCT WIDTH** | 52 mm |
| **PRODUCT WEIGHT** | 3.4 kg |
| **COMPLIANCES** | CB<br>LVD Directive<br>RoHS Directive<br>WEEE Directive<br>Packaging Directive<br>EMC Directive |
| **CERTIFICATIONS** | IEC 62368-1<br>EN IEC 63000<br>CE<br>EAC<br>UKCA<br>Cm<br>Ukr<br>IEC/EN 61000-6-2<br>IEC/EN 61000-6-4<br>EN 61000-3-2<br>EN 61000-3-3<br>CISPR 35/EN 55035 |
| **MODEL CODE** | PDU G4 MA 0U 309 16A 3P 12xC13,12xC39 |

## Additional information

| | |
|---|---|
| **ACCESSORIES** | • Rack PDU<br>• Rack mounting accessories<br>• Quickstart guide<br>• Safety Instructions |
| **COLOR** | Black |
| **MATERIAL** | Aluminium |
| **OPERATING TEMPERATURE** | 0° to 60°C (32° to 140°F) |

## Electrical output

| | |
|---|---|
| **NUMBER OF OUTLETS WITH EARTH PIN** | 24 |
| **NUMBER OF OUTPUTS (OTHER)** | 12 |
| **NUMBER OF OUTPUTS C13** | 12 |
| **NUMBER OF OUTPUTS C19** | 12 |
| **OUTLETS** | (12) C13, (12) C39 |

## Electrical input

| | |
|---|---|
| **AMPERAGE RATING** | 16A |
| **CORD LENGTH** | 3m |
| **FREQUENCY RATING** | 50/60 Hz |
| **INPUT CONNECTION** | IEC-60309 16A 3ph |
| **INPUT VOLTAGE** | 240/415V |
| **PHASE** | Three-phase |
| **WATTAGE** | 11 kW max |

## Technology & communications

| | |
|---|---|
| **ETHERNET INTERFACE** | Yes |
| **MASS CONFIGURATION** | Yes |
| **OUTLET CONTROL** | Yes |
| **SERIAL INTERFACE** | Yes |
| **SNMP** | Yes |
| **SPECIAL FEATURES** | • Remote Site Management<br>• Versatile C39 outlet supports C14 or C20 power cord plug<br>• High retention outlets designed to securely fit standard power cords and support P-Lock power cords<br>• Cybersecurity standards UL 2900-1 and IEC 62443-4-2<br>• Hot-Swap network control module<br>• Network Cascading, connect up to 32 PDUs via network loop<br>• Power sharing between two network modules PDUs ensures constant access to PDU data & sensors<br>• 1% IEC Class 1 billing grade measurement accurancy<br>• Gigabit network card with 2x Gb ports<br>• Support protocols RestAPI, Modbus TCP, SNMP, LDAP, HTTPS<br>• 1% measurement accuracy at the outlet level (V, W, A)<br>• Outlets control for On/Off, reboot, and sequential start-up capabilities |

| | |
|---|---|
| **TYPE** | Managed Rack PDU |

## Ressourcer

| | |
|---|---|
| **BROCHURER** | Eaton Rack PDU G4 Brochure EN |
| **BRUGERVEJLEDNINGER** | Eaton Rack PDU G4 Quick Guide |
| **DECLARATIONS OF CONFORMITY** | EU declaration of conformity Rack PDU G4 |
| **TEGNINGER** | Eaton Rack PDU G4 EVMAF316A technical drawing |

| | |
|---|---|
| **PROJEKTNAVN:** | |
| **PROJEKTNUMMER:** | |
| **KLARGJORT AF:** | |
| **DATO:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Irland
Eaton.com

Følg os på de sociale medier for at få de seneste produkt- og supportnyheder.

© 2026 Eaton. Alle rettigheder forbeholdt.