

NOBLO SPOT

white, 2700K, 36°, incl. 3-circuit adapter

Adjustable LED spot NOBLO with suitable adapter for the 240V 3-circuit track system. The luminaire impresses with its slim design and is therefore ideal for modern lighting concepts. The luminaire is made from aluminium and equipped with a Premium LED module.

TECHNICAL DATA

Item no.	1001866
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Track Ceiling,Track Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	7.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Level of inrush current	9 A
Duration of inrush current	23 µs
Stroboscopic effect (SVM)	0.03
Lumen	620 lm
Colour temperature	2700 Kelvin
Beam angle	36 °
Color	white
CRI	80

Light Source

916369	

LXXBXX data	L70B50
Service life	30000 h
Risk Group	1
Length	10.5 cm
Height	13.5 cm
Diameter	5 cm
Net weight	0.294 kg
Gross weight	0.411 kg
BIG WHITE Page	458