

@ansell_lighting
anselllighting
Ansell Lighting
ansell_lighting

EndLED

EndLED Lithium Exit Sign Maintained / Non-

Code: AENLED/LI/3M/ST

Category	Emergency
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance





PRODUCT FEATURES

- Low profile compact and modern polycarbonate LED exit box
- Self-test emergency as standard
- 20mm top and rear cable entries
- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- Supplied with all legend options - arrow down, arrow up and arrow left/right
- Available in black and white finishes

GENERAL INFORMATION	
Wattage	2.5W
Beam Angle	75
CRI	80
CCT	6000K
Input	220/240V
Operating Temp	5°C - 40°C
SDCM	5

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Wall
Lumen Depreciation	L70 53,000h
Warranty (Years)	6
CE Mark	Yes
Height	180 mm
Accessories	ASBP/18

EndLED

- Low profile compact and modern polycarbonate LED exit box
- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- Self-test emergency as standard
- Supplied with all legend options - arrow down, arrow up and arrow left/right
- 20mm top and rear cable entries
- Available in black and white finishes





Black

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CLASS	IP
220/240V	50/60Hz	5°C to 40°C	L70 53,000	2	IP20

CODE	DESCRIPTION	WATTAGE	CCT	VIEWING DISTANCE
AENLED/LI/3M/ST	Maintained / Non-Maintained - White	2.5W	6000K	30 metres
AENLED/LI/3M/ST/B	Maintained / Non-Maintained - Black			
AENLED/LI/3M/DA	Maintained / Non-Maintained - DALI - White	2.5W	6000K	30 metres
AENLED/LI/3M/DA/B	Maintained / Non-Maintained - DALI - Black			

CODE (ACCESSORIES)	DESCRIPTION
ASBP/18	3.2V 1500mAh Li-FePO4 Lithium Replacement Battery