ZUMTOBEL


TECTON C LED8000-840 L1500 WB LDE WH 42183328

LED continuous-row luminaire

Linear, energy-efficient TECTON LED continuous-row luminaire with 64 highly efficient mid-power LEDs per segment. Luminaire input power: 46 W, DALI controllable luminaire with LED converter, makes environmental and financial sense. LED service life lasts 100000 h before luminous flux is reduced to 95% of the initial value. Chromaticity tolerance (initial MacAdam): 2. Luminaire efficacy: 181 lm/W. Luminaire luminous flux: 8320 lm. Luminaire with symmetric wide light distribution (wide beam). Colour rendering Ra > 80, colour temperature 4000 K. Split lens concept for reducing perceived glare. Overlapping PMMA lenses (shatter-resistant to IK07) achieve IP50 protection for LED and optic. All-in-one solution: lighting batten, lamp and reflector are combined in one product to produce a 100 % continuous ribbon of LED light without gaps. High-quality look in a design that matches the trunking. Dimming level for DC mode preset to 15 %. LED continuous-row luminaire of sheet steel, enamelled in polyester lacquer finish, white. 100% flexible, tool-free mechanical and electrical installation using CLIX-technology by means of two side-mounted rotary levers on the TECTON trunking. No ultraviolet or infrared radiation. Ambient temperature -20 °C to 25 °C (ceiling surface-mounting), -20 °C to 35 °C (pendant mounting). Luminaire wired with halogen-free leads, silicone-free. Note: please talk to your adviser if you are planning to use the luminaire in environments containing chemical pollutants. Dimensions: 1498 x 60 x 85 mm. Weight: 2.2 kg.




ZS_TEC_F_LED_Balken.jpg



ZS_TEC_M_C_LED_Balken_L1500.wmf

Light Distribution STD - standard



TECTON_C_8000_840_L1500_WB_LDE_WH.ldt

- Light Source: LED
- Luminaire luminous flux*: 8320 lm
- Luminaire efficacy*: 181 lm/W
- Colour Rendering Index min.: 80
- Ballast: 1 x 28000657 LCA 75W 100-400mA one4all lp PRE
- Correlated colour temperature*: 4000 Kelvin
- Chromaticity tolerance (initial MacAdam): 2
- Rated median useful life*:
  L95 100000 h at -20 °C
  L95 100000 h at 35 °C
- Luminaire input power*: 46 W Power factor = 0.98
- Standby Power*: 0.15 W
- Control: LDE dimmable to 1%
  over DALI, DSI and switchDIM
  DC level is adjustable
- Maintenance category CIE 97: D - Enclosed IP2X
- Total harmonic distortion (THD): 6.50 %

This product contains a light source of energy efficiency class B.

Please also consult the additional information on the next page

IP20 IK07

We reserve the right to make technical changes without prior notice. 11.06.2026 © Zumtobel - 5-year guarantee in compliance with the terms of guarantee at www.zumtobel.com/guarantee

TECTON C LED8000-840 L1500 WB LDE WH 42183328

LED continuous-row luminaire

All values marked with an * are rated values. Leistung, Lichtstrom und ähnlichste Farbtemperatur können initial einer Toleranz von bis zu +/- 10% unterliegen. Unless stated otherwise, the values apply to an ambient temperature of 25°C.
The level of luminous flux reduces over the life cycle due to technological reasons. The failure of up to 4 LED points causes no functional impairment and is therefore no reason for complaint.
The failure of a complete lens cell causes reason for complaint

We reserve the right to make technical changes without prior notice. 11.06.2026 © Zumtobel - 5-year guarantee in compliance with the terms of guarantee at www.zumtobel.com/guarantee