ZUMTOBEL


RESPRO TEC-GP ANT E3D WH 42185793

Safety luminaire

LED emergency luminaire for antipanic lighting with min. 0,5 lux acc. to EN 1838; Room height 2.2 to 7 m; 2 high power LEDs, neutral white 4,000 K; lens made of polycarbonate; optimum thermal management via heat sink; TECTON module; Tool-free connection to TECTON continuous row system; roll-formed sheet steel with polyester paint finish; housing colour white (close to RAL9016); Luminaire with local battery supply for 3 h emergency lighting in maintained or non-maintained mode, with automatic test (auto-test) via the luminaire, optional central monitoring via DALI, display of luminaire status via status LED; NFC interface for addressing, configuration and maintenance via PROset Pen (article no.: 22170290) or PROset app; addressing also alternatively possible visually or via EZ-addressing; Maintained and non-maintained mode: +5 °C to +30 °C; power supply: 220-240 V AC (+/- 10 %), 50-60 Hz; Luminaire input power: 4.7 W (with battery fast-charging in maintained mode), typical connected load (without battery charging): 3.2 W in maintained mode / 1.1 W in non-maintained mode; Non-maintained and maintained mode settable via jumper and NFC interface; IP20; SC1; Luminaire wired with halogen-free and silicone-free leads; Impact strength: IK04; Dimensions: 500 x 60 x 85 mm; weight: 0.99 kg; Robust, integrated battery with 3-year warranty. Valid according to terms of the manufacturer's warranty, available at https://www.zumtobel.com/media/downloads/Garantiebedingungen_EN.pdf ; Battery warranty invalid if installation takes place three (3) months after delivery EXW (Incoterms 2010)




ZS_RES_F_PRO_TEC-GP_ExD_ANT_WH.jpg



ZS_RES_M_PRO_TEC-GP_ExD.wmf

Light Distribution STD - standard



D43617_RESC_PRO_TEC-GP_ANT_E3D_WH.ldt

- Light Source: LED
- Luminaire luminous flux*: 207 lm
- Total emergency luminous flux: 207 lm
- Luminaire efficacy*: 44 lm/W
- Colour Rendering Index min.: 70
- Ballast: 1 x 89800524 EM powerLED NTx 102 DIM 5W ZUM
- Chromaticity tolerance (initial MacAdam): 5
- Rated median useful life*: L95 100000 h at 25 °C
- Luminaire input power*: 4.7 W Power factor = 0.7
- Standby Power*: 1.2 W
- Charging power: 1.25 W
- Service life rating: 3 h
- Maintenance category CIE 97: D - Enclosed IP2X

This product contains a light source of energy efficiency class D.

Please also consult the additional information on the next page

IP20 IK04

We reserve the right to make technical changes without prior notice. 14.01.2026 © Zumtobel - 5-year guarantee in compliance with the terms of guarantee at www.zumtobel.com/guarantee

ZUMTOBEL

RESPRO TEC-GP ANT E3D WH 42185793

Safety luminaire

All values marked with an * are rated values. Connected electrical load and luminous flux are subject to an initial tolerance of +/- 10%, the most similar colour temperature is subject to an initial tolerance of +/- 150K. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

We reserve the right to make technical changes without prior notice. 14.01.2026 © Zumtobel - 5-year guarantee in compliance with the terms of guarantee at www.zumtobel.com/guarantee