Glamox

A3-W600 WH 1400 HF 830

A mirror luminaire with elegant Scandinavian design, soft lines, and rounded corners. Housing and diffusor in polycarbonate and can be equipped with PIR or microwave sensors, on/off or DALI controls. The luminaire can easily be mounted horizontally above or vertically beside the mirror.



Item No.	A3569354
GTIN	4741145693547
Stock status code	A

IP 44 Ta 40°

Technical specifications

Mounting	
Product Mounting	Wall surface

General	
Product shape	Linear

Electrical Data	
Main Feed AC (V) Min	220
Main Feed AC (V) Max	240
Main Feed Frequency Min	50
Main Feed Frequency Max	60
Total Consumption (W)	11
IEC Protection Class	II
Number Of Luminaire MCB 10B	35
Number Of Luminaire MCB 10C	58
Number Of Luminaire MCB 16B	56
Number Of Luminaire MCB 16C	93

Optic	
Optic Name	OP/PC - Opal diffuser in polycarbonate
Optic main category	Diffuser

Technical Data	
Maximum TA (°C)	40
IK classification	08
IP classification	44

Light Technical Data	
Light source	LED
Lumen Out (lm)	1376
Lumen Per Watt (lm/W)	123
Lamp colour temp (K)	3000
Colour Rendering Index	>80
MacAdam step	3

Driver / Ballast	
Type of LED Driver	HF: Non dimmable
Number of Driver	1

Lifetime	
LED Lifetime L80B50 Max Ta (h)	100 000
Driver lifetime at Ta=25, 10% failure rate (h)	100000
Luminous flux decline (LLMF) 50.000h Ta25	0.90

Housing	
Body Material	Polycarbonate
Body Colour	WH - White
Main Body Colour Name	White

Dimensions	
Length (mm)	599
Width (mm)	73
Height (mm)	73
Item Net Weight (kg)	1.0304

Cable Inlet	
Cable Gland	Grommet
Number of Glands	2

Sustainability	
Repairable/Changeable Parts	LED module;Internal driver;Optic;Sensor
Packaging Material	Recycled plastic;Cardboard;Recycled cardboard

Logistic Data	
Item Gross Weight (kg)	1.12

The Company reserves the right to change any product specifications without prior notification.

Illustrations



