LUXO

Air T80 BI 500 930 CLA EU



Air LED is a self-balancing task light with a spring-balanced arm for maximum reach and flexibility. It has perfect balance, and smooth movement that make it feel feather light – in spite of its steel construction.

Item No.	AIL024526
GTIN	7040670245267
Stock status code	A

CE EPD

Technical specifications

General	
Product shape	Task light
EPD (Environmental Product Declaration)	true

Electrical Data	
Leakage Current (mA)	0.2
Main Feed AC (V) Min	220
Main Feed AC (V) Max	240
Main Feed Frequency Min	50
Main Feed Frequency Max	60
Total Consumption (W)	7

Technical Data	
Maximum TA (°C)	25
IP classification	20

Light Technical Data	
Light source	LED
Lumen Out (lm)	501
Lumen Per Watt (lm/W)	72
Lamp colour temp (K)	3000
Colour Rendering Index	>90
MacAdam step	3
Energy Class Light Source	E

Lifetime	
LED Lifetime L80B50 Ta25 (h)	50 000
Luminous flux decline (LLMF) 50.000h Ta25	0.70

Housing	
Body Material	Steel
Body Colour	BL - Black
Main Body Colour Name	Black

Dimensions	
Length (mm)	160
Width (mm)	70
Height (mm)	42
Item Net Weight (kg)	1.3248

Sustainability	
Cradle To Gate A1-A3 (Kg C02-eq)	12.57
Total Recyclable Material %	51.13
Actual Recycled Material - EN15804 %	47.16
Repairable/Changeable Parts	External driver;Optic
Packaging Material	Recycled plastic;Recycled cardboard

Logistic Data	
Item Gross Weight (kg)	1.44

The Company reserves the right to change any product specifications without prior notification.

Illustrations





