# HSK-K

Item number 1209250030






Technical data

| | |
|---|---|
| **Material** | Polyamide V0 according to UL94 |
| **Seal** | NBR |
| **Protection class** | IP 54 , IP 68 with additional O-ring:IP68 - 10bar/30min , IP 69 K |
| **Type Rating by** | 12 , 4 , 4X , 6 (with additional O-ring) , UL 50E |
| **Temperature range** | -40°C to +100°C |
| **Colour** | grey |
| **RAL** | 7035 |
| **Variant** | Metric-long |
| **External thread (AG)** | M25 x 1,5 |
| **Cable diameter** | 13 - 18 mm |
| **Thread length (GL)** | 15 mm |
| **Height (H)** | 31 mm |
| **Wrench size (SW1/SW2)** | 33/33 mm |
| **Tightening torque** | 5 Nm |

# HSK-K

Item number 1209250030

Commercial data

| | |
|---|---|
| **Packaging Unit** | 50 |
| **EAN code** | 4033878410615 |
| **Weight** | 0.02254 kg |
| **ETIM 7** | EC000441 |
| **ETIM 8** | EC000441 |
| **ETIM 9** | EC000441 |
| **eCl@ss 10.1** | 27-14-44-32 |
| **Customs tariff number** | 39269097 |

Note: