
# HSK-W

Item number 1313160050






Technical data

| | |
|---|---|
| **Material** | Polyamide |
| **Seal** | NBR |
| **Material o-ring** | NBR |
| **Protection class** | IP 68 - 1bar/30min |
| **Temperature range** | -40°C to +100°C |
| **Colour** | grey |
| **RAL** | 7035 |
| **Variant** | Metric |
| **External thread (AG)** | M16 x 1,5 |
| **Cable diameter** | 4 - 8 mm |
| **Thread length (GL)** | 8 mm |
| **Height (H)** | 23 mm |
| **Length (L)** | 45 mm |
| **Wrench size (SW)** | 19 mm |
| **Tightening torque** | 2.5 Nm |
| **Type Rating by** | 12 , 4 , 4X , 6 (with additional O-ring) , UL 50E |

# HSK-W

Item number 1313160050

Commercial data

| | |
|---|---|
| **Packaging Unit** | 25 |
| **EAN code** | 4033878419625 |
| **Weight** | 0.0144 kg |
| **ETIM 7** | EC000441 |
| **ETIM 8** | EC000441 |
| **ETIM 9** | EC000441 |
| **eCl@ss 10.1** | 27-14-44-32 |
| **Customs tariff number** | 39269097 |

Note: