

# High mounting box

High mounting box, 73 mm

Type: AU5.32  
Product ID: 2TKA001740G1  
GTIN: 6418677335068



The AU5.32 mounting box is 73 mm high. The box has 2 branch inlets for Ø 20 conduit. There are also 3 knock-out inlets altogether at the side, and 2 at the bottom. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C).

## Technical specification

### Dimensions

|                   |       |
|-------------------|-------|
| For plastic pipe: | Ø20mm |
|-------------------|-------|

### Packing

|          |     |
|----------|-----|
| Package: | 50  |
| Unit:    | PCS |

### ETIM Data

|                    |                                      |
|--------------------|--------------------------------------|
| ETIM Version:      | ETIM-9.0                             |
| ETIM Class:        | EC002601                             |
| Mounting method:   | Flush mounted (plaster)              |
| Shape:             | Round                                |
| Construction type: | Device connection box (round/square) |

## Product Card

High mounting box, 73 mm



|                                            |            |
|--------------------------------------------|------------|
| Model:                                     | Single     |
| Provided with revolving ring:              | No         |
| Connectable:                               | Yes        |
| Equipped with:                             | None       |
| Diameter:                                  | 71 mm      |
| Length:                                    | 71 mm      |
| Width:                                     | 71 mm      |
| Depth:                                     | 71 mm      |
| Inner depth:                               | 72 mm      |
| For number of electric fittings:           | 1          |
| Mounting switching equipment:              | Screwing   |
| With screws:                               | Yes        |
| Housing feed-through by break-out opening: | Yes        |
| Housing feed-through by seal membrane:     | No         |
| Housing feed-through by nozzle:            | Yes        |
| Housing feed-through by step membrane:     | No         |
| For tube diameter:                         | 20/25 mm   |
| Pipe locking:                              | Yes        |
| Pipe locking optional:                     | No         |
| Inlet from the rear:                       | Yes        |
| Number of inlets:                          | 2          |
| Number of included spouts:                 | 2          |
| Material:                                  | Plastic    |
| Halogen free:                              | Yes        |
| Surface protection:                        | Untreated  |
| Colour:                                    | White      |
| Degree of protection (IP):                 | IP44       |
| Transparent cover:                         | No         |
| Cover attachment:                          | Snapped on |
| Sealable:                                  | No         |
| With screening:                            | No         |
| Air tight:                                 | No         |
| Clamp position fixed:                      | No         |
| Luminaire hook mounting:                   | No         |



|                      |      |
|----------------------|------|
| Special application: | None |
|----------------------|------|