O-range ECON® Fix one-gang junction box



LUFTDICHT

O-range ECON® Fix one-gang junction box, air-tight, Depth 62 mm

- Clamping ribs fastening in building materials from 10 mm thickness, e.g. wall constructions with OSB boards, gypsum fibre boards and exposed masonry
- 4 screw domes
- Air-tight design with sealing membranes
- Toolless cable or conduit entries
- Fully insulated, air-tight through-wiring for combinations using support connectors
- Integrated cable retention of the NYM cable, self-locking of the conduit
- including setting tool (Art. No. 1090-12) per packaging unit

Article no:	**9264-12**
EAN:	4013456551022
Depth	62 mm
Cut hole Ø	68 mm
Device screws +/-	2
Conduit entries up to Ø 25 mm	2
Cable entries 3 x 1.5 mm²	3
Cable entries 3 x 2.5 mm² or 5 x 1.5 mm²	3
Air-tight	Yes
Packaging inner/dispatch	25/250

With the O-range ECON® Fix junction box, installation is significantly faster and easier thanks to the latchless clamping ribs for fastening in various wall material combinations such as OSB boards, gypsum fibre boards or even in exposed masonry. Circumferential sealing lamellas on two levels guarantee that the airtight level is maintained. The centring bars enable convenient mounting of the device junction box in the installation opening without canting. PLUG - ALIGN - CLAMP - READY!

- Clamping rib fastening for different solid wall constructions
- Circumferential sealing lamellas on 2 levels to maintain the airtight level
- 4 screw domes for maximum flexibility for accessory fitting
- Toolless cable and conduit entry
- Device screws with +/- drive

O·range ECON® air-tight IP 30 850 °C INNOVATION