# Specifications




## Eaton 248345

Eaton Distribution board accessory, Two way switchp11 CO, 16A, 230 V, 20kA, I-0-II

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton distribution board accessory |
| **CATALOG NUMBER** | 248345 |
| **MODEL CODE** | Z-S/WM |
| **EAN** | 4015082483456 |
| **PRODUCT LENGTH/DEPTH** | 80 mm |
| **PRODUCT HEIGHT** | 75 mm |
| **PRODUCT WIDTH** | 17.5 mm |
| **PRODUCT WEIGHT** | 0.063 kg |
| **COMPLIANCES** | RoHS conform |

## Product specifications

| | |
|---|---|
| **RATED OPERATIONAL VOLTAGE (UE) - MAX** | 240 V |
| **WIDTH IN NUMBER OF MODULAR SPACINGS** | 1 |
| **NUMBER OF POLES** | Single-pole |
| **COLOR CALOTTE** | Other |
| **SWITCH TYPE** | Two-way switch |
| **RATED SHORT-TIME WITHSTAND CURRENT (ICW)** | 10 kA |
| **LAMP SOCKET** | Other |
| **BUILT-IN DEPTH** | 80 mm |
| **AMPERAGE RATING** | 20 A |
| **VOLTAGE TYPE** | AC |
| **LAMP TYPE** | Other |
| **DEGREE OF PROTECTION** | IP40 |
| **NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)** | 1 |
| **NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)** | 0 |
| **NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)** | 0 |
| **INSCRIPTION** | Other |
| **RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)** | 20 A |
| **RATED SWITCHING CAPACITY** | 0.02 kA |

## Resources

| | |
|---|---|
| **DECLARATIONS OF CONFORMITY** | eaton-distribution-parts-declaration-of-conformity-eu250341en.pdf |
| **MCAD MODEL** | eaton-universal-control-switches-mcad-3d-models-z-s-switch-1w.stp<br><br>eaton-universal-control-switches-mcad-drawings-z-s-switch-1w.dwg |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.