Specifications

Eaton 167595

Eaton Moeller series xPole - SPCT2 Surge Protection Device. Plug-in surge arresters, 3p, 280VAC, 3x20kA

General specifications	
PRODUCT NAME	Eaton Moeller series xPole - SPCT2 Surge protection device
CATALOG NUMBER	167595
MODEL CODE	SPCT2-280/3
EAN	4015081640669
PRODUCT LENGTH/DEPTH	85 mm
PRODUCT HEIGHT	67 mm
PRODUCT WIDTH	52.5 mm
PRODUCT WEIGHT	0.311 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	CE

Additional information

FEATURES	Category type 2
SYSTEM CONFIGURATION TYPE	TN TN-C Other TN-S

Delivery program

APPLICATION	• Open areas • Residential buildings • Utility buildings
TYPE	Surge arrester

Technical data - electrical

CONTINUOUS VOLTAGE AT AC - MAX	280 V
DISCHARGE SURGE CURRENT (8/20) - MAX	40 kA
NOMINAL DISCHARGE SURGE CURRENT (8/20)	20 kA
NOMINAL VOLTAGE AT AC	280 V
SIGNALLING AT THE DEVICE	Optic
VOLTAGE PROTECTION LEVEL	1.4 KV

Technical data - mechanical

CONDUCTOR CROSS SECTION (FLEXIBLE, FINE-STRAND) - MAX	35 mm²
CONDUCTOR CROSS SECTION (FLEXIBLE, FINE-STRAND) - MIN	35 mm²
CONDUCTOR CROSS SECTION (SOLID, SOLID-STRAND) - MAX	25 mm²
CONDUCTOR CROSS SECTION (SOLID, SOLID-STRAND) - MIN	25 mm²
DEGREE OF PROTECTION	IP20
FRAME	3 modular spacing
MOUNTING METHOD	DIN rail (top hat rail) 35 mm
NUMBER OF CONDUCTORS WITHOUT EARTHING	3

Resources

DECLARATIONS OF CONFORMITY	eaton-surge-protection-device-declaration-of-conformity-eu250063en.pdf
INSTALLATION INSTRUCTIONS	eaton-surge-protection-spct2-il019017zu.pdf
INSTALLATION VIDEOS	xpole-spct2-installation-video
MCAD MODEL	eaton-combined-arrestor-mcad-drawings-sp-3p.dwg eaton-combined-arrestor-mcad-3d-models-sp-3p.stp
PEP ECO-PASSPORT	eaton-t2-arrestor-pep-eato-00260-v0101-en.pdf

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.