

Eaton 35NHG000B

Catalog Number: 35NHG000B

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 500V, 35A, 120 kAIC, Combination fuse status indicator, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Metal plated copper contact plate, Ceramic body

Photo is representative

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	35NHG000B
	EAN
	5027590477819
UPC	Product Length/Depth
051712625814	79 mm
Product Height	Product Width
51 mm	21 mm
Product Weight	Compliances
0.117 kg	RoHS Compliant
	CE Marked
Certifications	
IEC 60269-1	
IEC 60269-2	
DIN 43620	



Electrical data

Amperage Rating

35 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

120 kA

Class

Class gG/gL

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

Fuse size

NH000

Insulated metal gripping lugs (IMGL)

No

Accessories

Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

Resources

Catalogues

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[NH Fuse links, bases and gear](#)

[CA134002EN](#)

Declarations of conformity

[UKCA NH Size 000, 500V fuse-links](#)

[CE NH Size 000, 500V fuse-links](#)

eCAD model

[eaton-low-voltage-nh-fuse-eplan-35nhg000b.edz](#)

Multimedia

[Eaton Bussmann – NH fuse link portfolio](#)

Presentations

[NH Overview Video](#)

Technical data sheets

[10164 NH 500 Volts gG](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2025 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)