Specifications



Eaton C22G80

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 80 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH22 Modular fuse holder

General specifications	
PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C22G80
MODEL CODE	CYLINDRICAL FUSE 22 x 58 80A GG 500V AC
EAN	5027590495561
UPC	051712754507
PRODUCT LENGTH/DEPTH	58 mm
PRODUCT HEIGHT	22.2 mm
PRODUCT WIDTH	22.2 mm
PRODUCT WEIGHT	55 g
COMPLIANCES	CE Marked GoST-R RoHS Compliant
CERTIFICATIONS	IEC 60269

Compatible fuse holders

SUITABLE FOR	CH22 Modular fuse holder

Electrical data

AMPERAGE RATING	80 A
BREAKING CAPACITY	120 kA
FREQUENCY RATING - MAX	62 Hz
UTILIZATION CATEGORY	gG (cable protection/equipment protection)
VOLTAGE RATING	500 V
VOLTAGE TYPE	AC

Resources

CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf eaton-bussmann-series-low-voltage-fuses-catalog-ca134002en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-uk250946en.pdf
MCAD MODEL	eaton-iec-lv-fuses-mcad-3d-models-2-125a-c22x58.stp eaton-iec-lv-fuses-mcad-drawings-2-125a-c22x58.dwg
MULTIMEDIA	Video Cylindrical fuse link portfolio
TECHNICAL DATA SHEETS	720115 Cylindrical fuses

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.