Specifications



Eaton 263155

Eaton Fuse switch disconnector, Single-pole, 16 A, D01

General specifications	
PRODUCT NAME	Eaton distribution board accessory
CATALOG NUMBER	263155
MODEL CODE	Z-SLS/D01/1
EAN	4015082631550
PRODUCT LENGTH/DEPTH	89 mm
PRODUCT HEIGHT	70 mm
PRODUCT WIDTH	18 mm
PRODUCT WEIGHT	0.09 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC/EN 60947-3

Product specifications

AMPERAGE RATING	16 A
FRAME	Standard front dimension: 45 mm
CREEPAGE RESISTANCE	CTI 600
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	2 W
RATED OPERATIONAL VOLTAGE (UE) - MAX	230 V
RATED SHORT-CIRCUIT MAKING CAPACITY UP TO 690 V, 50/60 HZ	50 kA
RATED UNINTERRUPTED CURRENT (IU)	16 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	0 W
TERMINALS	Lift terminals
NUMBER OF POLES	Single-pole
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6 kV
DEGREE OF PROTECTION	IP20
RATED UNINTERRUPTED CURRENT (IU) AT MAX. CROSS SECTION	16 A
SWITCHING CATEGORY	AC 22 B, DC 21 B
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
CURRENT HEAT LOSS PER CONTACT AT IE	0.64 W
ENCLOSURE WIDTH	86 mm
HEAT DISSIPATION PER CONTACT WITH FUSE LINK AT IE	2.24 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	2 W
CONSTRUCTION SIZE	D01
FUNCTIONS	Fuse switch-disconnector Z-SLS/D01
OVERVOLTAGE CATEGORY	IV
FUSE CARTRIDGE	D01: 2 - 16 A
MOUNTING METHOD	Quick attachment for top-hat rail IEC/EN 60715
RATED OPERATION CURRENT (IE)	16 A
VOLTAGE RATING	230 V AC
FLAMMABILITY CHARACTERISTICS (UL)	V0, glow-wire test 960 °C (UL94)
TYPE	Fuse material

Resources

SPECIAL FEATURES	• Standard, empty • With flashing function • Suitable for fuses, utilisation class gG (gL), aM • Current coding built-in • sealable • Infeed possible from both sides
MOUNTING WIDTH	17.5 mm per pole (1 space unit)
TERMINAL CAPACITY (SOLID CABLE)	1.5 mm² - 25 mm²
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	16 A

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.