

348170249024

Ultra-slim PCB Relay (EMR or SSR) 0.1 - 0.2 - 2 - 6 A






This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

Subminiature PCB relays, Solid State (SSR), 1 NO (SPST-NO), 6 A, 6 A - 24 V DC, DC input version, nominal voltage 24 V, operating from 16 to 30 V, rated power 0.17 W, consumption 7 mA, must drop-out voltage 10 V, impedance 3430 Ω, ambient temperature from -20 to +70 °C

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-20...70 °C
Commercial Description:	Solid state relay for printed circuit mount, direct or via PCB socket. Also for 35 mm rail mount via screw, screwless or push-in terminal sockets
Contact configuration:	1 NO (SPST-NO)
Dimensions:	15.6x5x28 mm
Electrical life:	0 cycles
Nominal voltage DC:	24 V
Operating range DC:	16...30 V
Rated current (contacts):	6 A
Rated power DC:	0.17 W
Supply:	DC input version
Certifications and quality approvals (according to type):	<div></div>

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)