


386100240060

Relay interface module (EMR or SSR) 0.1 - 2 - 3 - 5 - 6 - 8 - 16 A






This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

Relay interface modules, Electromechanical relay, with screwless terminal, 1 pole, CO (nPDT), 6 A, AgNi, AC/DC coil, 24 V, operating from 19.2 to 26.4 V (AC)/(DC), rated power 0.3 VA (AC) / 0.2 W (DC), consumption 12 mA, holding voltage 14.4 V (AC)/(DC), must drop-out voltage 2.4 V (AC) and 1.2 V (DC), option: AC or AC/DC, version: CO (nPDT), ambient temperature from -40 to +55 °C

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...55 °C
Commercial Description:	Electromechanical relay interface module with screwless terminals, 1 CO rated 6 A/250 V AC, 6.2 mm wide, 35 mm rail (EN 60715) mounting, for PLC or other systems.
Contact configuration:	1 pole, CO (nPDT)
Dimensions:	6.2x93.6x72.5 mm
Electrical life:	60000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage AC:	24 V
Nominal voltage DC:	24 V
Operating range AC:	19.2...26.4 V
Operating range DC:	19.2...26.4 V
Rated contact voltage:	250 V AC
Rated current (contacts):	6 A
Rated power AC:	0.3 VA
Rated power DC:	0.2 W
Supply:	AC/DC coil
Certifications and quality approvals (according to type):	<div>CE</div> <div></div> <div>EAC</div> <div></div> <div></div> <div>UKCA</div>

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)