
388170248240

Relay interface module (EMR or SSR) 0.1 - 2 - 3 - 5 - 6 - 8 - 16 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:
Relay interface modules, timer SSR 14 mm wide, with screwless terminal, 2 A, 2 A - 240 V AC, DC input version, nominal voltage 24 V, operating from 16.8 to 30 V, rated power 0.3 W, consumption 10.5 mA, must drop-out voltage 10 V, ambient temperature from -20 to +55 °C

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-20...55 °C
Commercial Description:	SSR interface module with screw terminals. High switching speed and long electrical life. Single pole SSR output – AC or DC switching, DC or AC/DC input, 35 mm rail mounting (EN 60715). Ideal for PLC and electronic systems.
Contact configuration:	1 NO
Dimensions:	6.2x88.4x72.1 mm
Nominal voltage DC:	24 V
Operating range DC:	16.8...30 V
Rated contact voltage:	240 V AC
Rated current (contacts):	2 A
Rated power DC:	0.3 W
Supply:	DC input version
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form
the basis of a contract.

Need more information?
Contact our sales Find a dealer

Finder 2025 - All rights reserved
Findernet.com
Technical Information