
406182300000

Pcb plug in relay 16a



Technical description: Miniature PCB Relays, PCB/Plug-in – 5 mm pinning, 1 pole, CO (nPDT), 16 A, AgCdO, AC coil, 230 V, operating from 184 to 253 V, rated power 1.2 VA, resistance 28000 Ω, consumption 5 mA, holding voltage 184 V, must drop-out voltage 46 V, option: Pin length 5.3 mm (Plug-in relays), version: Flux proof (RT II), ambient temperature from -40 to +85 °C

Commercial description: Miniature PCB relay, 1 CO 16 A. PCB mount (5.0 mm pin pitch) or plug-in with 95 Series sockets, DC coils (650 mW or 500 mW) and AC coils. Variant with Cadmium-free contacts. 8 mm, 6 kV (1.2/50 µs) insulation between coil and contacts. Complies with the glow wire test according to EN 60335-1..

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-40...85 °C
Contact configuration:	1 pole, CO (nPDT)
Dimension:	12.4x25x29 mm
Electrical life:	100000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage ac:	230 V
Operating range ac:	184...253 V
Rated current contact:	16 A
Rated power ac:	1.2 VA
Rated voltage contact:	250 V AC
Supply version:	AC coil
Type:	PCB/Plug-in – 5 mm pinning
Certifications and quality approvals (according to code):	

Need more information?

Contact our sales Find a dealer

Finder 2023 - All rights reserved
Findernet.com
Technical Information

All the data displayed in this file are automatically generated by our online catalogue.
Complete data can be found in the user documentation.
Creation Date 20/11/2023.