
466182300040

Miniature Industrial relay 8 - 16 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:
Miniature Industrial relay, Spade/blade terminal Faston, 1 pole, CO (nPDT), 16 A, AgNi, AC coil, 230 V, operating from 184 to 253 V, rated power 1.2 VA, resistance 28000 Ω, consumption 5 mA, holding voltage 184 V, must drop-out voltage 46 V, option: Lockable test button + mechanical indicator, ambient temperature from -40 to +70 °C

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-40...70 °C
Commercial Description:	Miniature industrial relay with 1 CO 16A contact for socket mount or direct connection via Faston connectors. Equipped with AC or DC coil. Available with: lockable test button and mechanical and LED indicator. With Cadmium-free contacts. European patent.
Contact configuration:	1 pole, CO (nPDT)
Dimensions:	12.4x32.8x29 mm
Electrical life:	100000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage AC:	230 V
Operating range AC:	184...253 V
Rated contact voltage:	250 V AC
Rated current (contacts):	16
Rated power AC:	1.2 VA
Supply:	AC coil
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form
the basis of a contract.

Need more information?
Contact our sales Find a dealer

Finder 2026 - All rights reserved
Findernet.com
Technical Information