863000240000

Timer modules



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:
Timer modules, Bi-function, See 40, 46, 55, 56, 60 and 62 Series relays, for changeover ATEX see 58 ATEX series., AC/DC supply version, nominal voltage 24 V, operating from 9.6 to 33.6 V (AC)/(DC), rated power 0.15 W, ambient temperature from -20 to +50 °C

BROWSE PRODUCT PAGE

Technical Features:

Commercial Description:	Bi-function and multi-voltage plug-in timer modules with time scales from 0.05 s to 100 h. For use with Type 90.02, 90.03, 92.03, 94.P3, 94.P4, 94.02, 94.03, 94.04, 95.P3, 95.P5, 95.03, 95.05, 96.02, 96.04, 97.P1, 97.P2, 97.01 and 97.02 sockets. Available ATEX compliant version (Ex ec) - HazLoc Class I Div. 2 Group A, B, C, D - T6. Plug-in for use with 94.0x.7 socket.
Delay setting:	(0.05...1)s, (0.5...10)s, (5...100)s, (0.5...10)min, (5...100)min, (0.5...10)h, (5...100)h
Dimensions:	15.5x11.3x31 mm
Functions:	Bi-function
Nominal voltage:	24 V
Operating range AC:	9.6...33.6 V
Operating range DC:	9.6...33.6 V
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form
the basis of a contract.

Need more information?
Contact our sales Find a dealer

Finder 2025 - All rights reserved
Findernet.com
Technical Information